DATA SHEET

COD. 20034607W

3.5" MINITOUCH SIMPLEHOME SUPERVISOR - WHITE

Mini-Touch 3,5" with a supervisory function. To be connected to BUS SimpleHome for the management of the automation system to control lights, loads, shutters, climate, scenary and the irrigation system and to SimpleSafe system for visualisation and operation of the burglar alarm syste . Integrated temperature sensor, 1 changeover relay output. RFID integrated reader to activate scenarios from transponder art.SK9050. RGB adjustable and Magic Light Indicator function with change of colour depending on the status of the areas climate and according to the status of the burglar system. Suitable for installation on standard box 3 modules or civil series. size 125x85mm. 10mm projection wall. Consumption 2W.



General specifications

Backlighting colour: BLUE

Compatibility

Antintruder family:	Yes
Home automation family:	Yes

Mounting/Installation

Flush-mounted:	Yes
Flush-mounted box type:	3 moduli serie civile
Wall-mounted:	No

Audio/video specifications

Display size (inches):	3,5
B/W or colour display:	COLOR
Touch screen display:	Yes
Display resolution:	320 RGB x 240
Type of display:	TFT

Hardware specifications

SIM slot:	No
Customisable housing:	No
Removable terminals:	No

Software/firmware specifications

No. scenarios:	50
No. conditioned scenarios:	Yes



DATA SHEET

· · · · · · · · · · · · · · · · · · ·	
Weekly programming:	Yes
onnectivity	
No. of Simplehome buses:	1
RS485 ports:	1
The 100 porto.	•
ınctions - Settings	
Bridging function from automation to anti-intrusion:	Yes
Anti-intrusion management:	Yes
Automation management:	Yes
Loads management:	Yes
Climate management:	Yes
Logic management:	No
Lights management:	Yes
Scenario management:	Yes
Temperature sensor management:	Yes
Timing management:	Yes
CCTV management:	No
Display colour control:	Yes
Display contrast control:	Yes
Display brightness control:	Yes
chainel areacution	
chnical properties Proximity reader RFID:	Yes
Troximity reduct it ib.	163
ectrical specifications	211/
	2W
ectrical specifications Absorption:	2W
ectrical specifications Absorption: eneral info	
ectrical specifications Absorption: eneral info Intrastat code:	85361010
ectrical specifications Absorption: eneral info Intrastat code: Product height (mm):	85361010 85
Absorption: Absorption: Absorption: Absorption: Absorption: Intrastat code: Product height (mm): Product width (mm):	85361010 85 125
ectrical specifications Absorption: eneral info Intrastat code: Product height (mm): Product width (mm): Product depth (mm):	85361010 85 125 10
Absorption: Peneral info Intrastat code: Product height (mm): Product width (mm):	85361010 85 125
Absorption: Peneral info Intrastat code: Product height (mm): Product width (mm): Product depth (mm): Product colour:	85361010 85 125 10
Absorption: Peneral info Intrastat code: Product height (mm): Product width (mm): Product depth (mm): Product colour:	85361010 85 125 10
Absorption: Absorption: Absorption: Absorption: Absorption: Intrastat code: Product height (mm): Product width (mm): Product depth (mm): Product colour: Ackaging Single pack height (mm):	85361010 85 125 10 BLACK
Absorption: Peneral info Intrastat code: Product height (mm): Product depth (mm): Product colour: Ackaging Single pack height (mm): Single pack width (mm):	85361010 85 125 10 BLACK 60 160
Absorption: Absorption: Absorption: Absorption: Absorption: Intrastat code: Product height (mm): Product width (mm): Product depth (mm): Product colour: Ackaging Single pack height (mm):	85361010 85 125 10 BLACK

