## **DATA SHEET**

## сор. 20046912

## SIMPLEHOME FLUSH-MOUNTED INTERFACE WITH TWO 6 A RELAYS

Flush-mounted interface with two 6 A relays, 2 N.O. outputs with single common reference. Ideal for controlling shutters or resistive loads up to 6 A. Not suitable for controlling fluorescent, LED and low energy lights or high loads. For connection to 24 Vdc transistor outputs (for example, module art. 20046502).



Compatibility   Yes     Home automation family:   Yes     Mounting/Installation   Yes     Flush-mounted:   Yes     DIN rail mounted:   No     Hardware specifications   Yes     Removable terminals:   Yes     Technical properties   0/50     Temperature range:   0/50	
Mounting/Installation     Flush-mounted:   Yes     DIN rail mounted:   No     Hardware specifications   Removable terminals:     Removable terminals:   Yes     Technical properties   0/50	
Flush-mounted:   Yes     DIN rail mounted:   No     Hardware specifications   Yes     Removable terminals:   Yes     Technical properties   Yes     Temperature range:   0 / 50	
Flush-mounted:   Yes     DIN rail mounted:   No     Hardware specifications   Yes     Removable terminals:   Yes     Technical properties   Yes     Temperature range:   0 / 50	
DIN rail mounted: No   Hardware specifications Yes   Removable terminals: Yes   Technical properties   Temperature range: 0 / 50	
Hardware specifications      Removable terminals:   Yes     Technical properties   0 / 50	
Removable terminals: Yes   Technical properties 0 / 50	
Removable terminals: Yes   Technical properties 0 / 50	
Technical properties     Temperature range:   0 / 50	
Temperature range: 0 / 50	
Temperature range: 0 / 50	
General info	
EAN product code: '8023903192667	
Intrastat code: 85361010	
Packaging	
Single pack height (mm): 40	
Single pack width (mm): 86	
Single pack weight (g): 60	
Single pack depth (mm): 56	
Single pack volume (dm3): 0,193	



The technical specifications are subject to variations without warning