

MINI series door-entry phone for Simplebus system with electronic call, key button and additional button for extra services (switchboard call, actuator, generic uses). Call volume and privacy adjustment by means of 3-position selector. Privacy activation is indicated by a red light. Allows floor door call management. Complete with 8-position dip-switch for selection of the desired user code. Dimensions: 105x191x28 mm



2708W

## DOOR-ENTRY PHONE W/ 2 BTNS FOR SIMPLEBUS AUDIO. MINI SER.

GENERAL SPECIFICATIONS	
Audio system:	Yes
Audio/video system:	No
Flush-mounted:	No
Wall-mounted:	Yes
Desk base-mounted:	Yes
Hands-free function:	No
Induction loop function:	No
Product colour:	White
Sensitive Touch technology:	No
Total buttons:	2

## FUNCTIONS

Actuator control function:	Yes
Switchboard call function:	Yes
Intercom function:	No
Selective intercom call:	No
Privacy function:	Yes
Doctor:	No
Floor door call function:	Yes
Electronic bell:	Yes
Customisable ringtone:	No
Key button function:	Yes

SETTINGS	
Loudspeaker volume control:	Yes
Ringtone volume control:	Yes

GENERAL DATA	
Product height (mm):	190
Product width (mm):	103
Product depth (mm):	30

COMPATIBILITY	
Simplebus Top audio/video system:	Yes

TECHNICAL SPECIFICATIONS	
Power supply voltage: ÷	÷ 20



2708W

## DOOR-ENTRY PHONE W/ 2 BTNS FOR SIMPLEBUS AUDIO. MINI SER.

TECHNICAL SPECIFICATIONS	
Absorption in standby (mA):	0,715
In called absorption (mA):	23,00
In communication absorption (mA):	22,00
Microphone:	9,6x6,9mm omni-direction
Loudspeaker:	Ø 0,50 mm ; Max Imput Power 0,5W
IP Rating:	IP30
Operating temperature (°C):	÷-5
Product weight (g):	257
Clamps:	L,L,CFP,CFP