



**2738W/A**

## **SIMPLEBUS2 MINI DOOR ENTRY PHONE WITH HANDSET**



Mini series door-entry phone with handset for Simplebus 2 audio systems. Equipped with a key button, button for additional services such as calls to the porter switchboard..., call volume adjustment, Silent mode (Privacy) and floor call input. Correct positioning of the handset on the base is facilitated by invisible magnetised panels. The additional board art. 2735 is available to purchase separately, for an additional button with voltage free contacts and call repetition.

### **AWARDS**

DESIGN  
MILANO



**2738W/A**

**SIMPLEBUS2 MINI DOOR ENTRY PHONE WITH HANDSET**

**GENERAL DATA**

Product height (mm)	190
Product width (mm)	103
Product depth (mm)	28
Material	ABS
Product weight (g)	300
Product color	White RAL9003

**COMPATIBLE SYSTEMS**

Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Simplebus 2 audio/video kit with power supply art. 1209	Yes
Audio Simplebus 2 with power supply art. 1210/1210A	Yes

**AUDIO FEATURES**

Technologies implemented	Full-Duplex
--------------------------	-------------

**ELECTRICAL CHARACTERISTICS**

Type of power supply	Power supply from video door entry bus
----------------------	--

**HARDWARE FEATURES**

Type of buttons	Mechanical
Service buttons	Lock-release
Number of inputs (n°)	1

**SETTINGS**

Ringtone volume	Yes
-----------------	-----

**ENVIRONMENTAL AND COMPLIANCE FEATURES**



**2738W/A**

**SIMPLEBUS2 MINI DOOR ENTRY PHONE WITH HANDSET**

Operating humidity (RH max - %) (%)	25 ÷ 75
Environmental class	III
Compliance and Certifications	RoHS II - 2011/65/UE (EN 50581:2012), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

**MAIN FUNCTIONS**

Door opener	Yes
Actuator control	Yes
CPS call	Yes
Outside door call input	Yes
Silent mode (Privacy)	Yes

**MAIN FEATURES**

Wall-mounted	Yes
Desk base-mounted	Yes, with a dedicated accessory

**TECHNICAL CHARACTERISTICS**

Supply voltage	22÷35VDC
Maximum absorption (W)	0.8
Microphone	9.6 (∅) x 6.9mm, omnidirectional
Loudspeaker	50mm (∅), 50 Ohm, 0.25W
Operating temperature (°C)	-5 ÷ 40
Clamps	L L CFP CFP