



3005XVB

316 ANALOG AUDIO/VIDEO ENT.PAN., 5 BUTTONS 2 WIRES



Flush-mounted entrance panel (fitted level with the wall) and plate in 3mm thick 316 stainless steel; buttons integrated into the plate, with no mechanical movement. IK08 certification. Nameplates with LED lighting and front access for name replacement. Allows management of visual call, conversation and door lock status indications. Complete with a/v unit Art. 4681 for audio/video/door lock management, and flush-mounted box with concealed fixing screws. Dimensions 342x182x3 mm



3005XVB

316 ANALOG AUDIO/VIDEO ENT.PAN., 5 BUTTONS 2 WIRES

MAIN SPECIFICATIONS

Audio/video system:	Yes
Flush-mounted:	Yes
Horizontal resolution (TVL):	420
Maximum current absorption (mA):	450
Total buttons:	5
Loudspeaker volume control:	Yes
Operating temperature (°F):	-13 ÷ 131
Vandal Resistant rating (IK code):	IK08
S/N ratio (dB):	48
Video output:	1Vpp 75PAL

SOFTWARE/FIRMWARE SPECIFICATIONS

Video resolution (H x V):	
---------------------------	--

HARDWARE SPECIFICATIONS

Visual signalling:	Yes
Acoustic signalling:	Yes
Sensitive Touch technology:	Yes

GENERAL DATA

Product depth (inches):	2.36
-------------------------	------

COMPATIBILITY

Simplebus Top audio/video system:	Yes
-----------------------------------	-----

TECHNICAL SPECIFICATIONS


Sensitivity (lux):	1
Type of camera:	



3005XVB

316 ANALOG AUDIO/VIDEO ENT.PAN., 5 BUTTONS 2 WIRES

ACCESSORIES



1220

NAME TAG SHEETS FOR 316 ANALOG ENTRANCE PANEL

The kit contains 10 sheets of adhesive labels for nameplates and 7 sheets for information modules.



1235A

NAMEPLATE LABEL PRINTING SOFTWARE

Dedicated software for the creation and printing of nameplate and information labels for Ikall, Vandalcom, Quadra and 316 Analog entrance panels. Requires use of adhesive labels art.1217, 1218, 1219 or art.1220. This software is available to download free of charge from the Comelit website



1596B

POWER SUPPLY 33VDC 60W 100-240VAC, PSE CERTIFIED

Power supply unit with 110-230 VAC primary and 33 VDC / 1.8A continuous output for 316 range entrance panels. Equipped with internal protection against current overload and short circuits. Dimensions: 4.17"x3.5"x2.44" (6 DIN modules). PSE certified.



3458

ACCESS CONTROL ACCESSORY MODULE FOR EXTERNAL UNITS, 316

Flush-mounted 3 mm thick stainless steel plate for housing the access control module. Can be used in conjunction with all entrance panels in the 316 range. Dimensions 88x182x3 mm



3459

RAINSHIELD WITH LEDS FOR 316 SENSE ST. STEEL ENT. PANEL

Rain shield for 316 series panels.



3460/12

FLUSH-MOUNTED BOX FOR 10-11-12-BUTTON ENT.PANELS. 316 SERIES

Flush-mounted box for 10-, 11- and 12-button ent. panels from 316 Analog series. Dimensions: 164x457.5x56 mm



3005XVB

316 ANALOG AUDIO/VIDEO ENT.PAN., 5 BUTTONS 2 WIRES



3460/2

FLUSH-MOUNTED BOX FOR 1- AND 2-BUTTON ENT.PANELS. 316 SERIES

Flush-mounted box for 1- and 2-button ent. panels from 316 Analog series. Dimensions: 164x227.5x56 mm



3460/4

FLUSH-MOUNTED BOX FOR 3- AND 4-BUTTON ENT.PANELS. 316 SERIES

Flush-mounted box for 3- and 4-button ent. panels from 316 Analog series. Dimensions: 164x273.5x56 mm



3460/6

FLUSH-MT.BOX FOR TOUCH-SENSE & 5-6 BUTT.ENT.PAN. 316 SERIES

Flush-mounted box for 5- and 6-button ent. panels from 316 Analog series and for 316 Touch and 316 Sense series ent. panels. Dimensions: 164x323x56 mm



3460/9

FLUSH-MOUNTED BOX FOR 7-8-9-BUTTON ENT. PANELS. 316 SERIES

Flush-mounted box for 7-, 8- and 9-button ent. panels from 316 Analog series. Dimensions: 164x388.5x56 mm



3462/2

WALL-MOUNTED HOUSING SERIES 316 1 & 2 BUT. PANEL

Stainless steel accessory for wall-mounted 316 series entrance panels with 1 or 2 buttons. Dimensions 180x245x57 mm



3462/4

WALL-MOUNTED HOUSING SERIES 316 3 & 4 BUT. PANEL

Stainless steel accessory for wall-mounted 316 series entrance panels with 3 or 4 buttons. Dimensions 180x290x57 mm



3005XVB

316 ANALOG AUDIO/VIDEO ENT.PAN., 5 BUTTONS 2 WIRES



3462/6

WALL HOUSING FOR TOUCH-SENSE & 5-6 BUTT.ENT.PAN. 316 SERIES

Stainless steel accessory for wall-mounted entrance panels Art. 3451, 3451/A, 3452, 3453, 3454. Dimensions 180x340x57 mm



3501

Single-plate AV with BM and 1 button. 2-wire



3501VG

Single-plate AV with BM and 2 buttons, 2-wire



3502

Single-plate AV with BM and 4 buttons, 2-wire



3504



1595

33VDC POWER SUPPLY UNIT FOR IKALL ENTRANCE PANEL

Power supply unit 110-230V input and 33Vdc 500 mA continuous output, and 1.2A inrush current for external unit with IKALL entrance panel. Equipped with internal protection against overcurrent and short circuits. Dimensions: 71.7x90x62 mm (4 DIN modules).