



The compact construction form of the effeff 332.238 escape door strike allows rapid, uncomplicated mounting in a wide variety of profiles and door frames

ProFix® is a combined system, consisting of a FaFix® electric strike with a latch bolt guide (latch bolt slide) integrated into the electric strike. effeff has developed ProFix to enable users to take full advantage of radius electric strikes and FaFix®. ProFix® can be used to standardise frame/glazed frame cut-outs.

#### Overview of Advantages

- Radius latch
- Compact symmetrical design
- Min. 2000 N, max. 3000 N holding power according to prEN13633 and prEN 13637
- Unlocking under preload with 100% holding power
- Monitoring contact is potential-free and armature contact is non-isolated \*
- Suitable for DL/DR and horizontal installation
- Compact fitting dimensions
- Adjustable FaFix® latch: 2 mm adjustment range with 0.5 mm increments
- Compatible with ProFix® 2 striking plates
- Monitoring contact integrated in housing
- Monitoring flap moves together with the FaFix® screw-on attachment, i.e. the switching point always remains the same

#### Scope of delivery

- 1 piece escape door strike

Technical data	
Voltage	24 V DC
Adjustable latch (FF, FaFix®)	Yes
Monitoring contact (RR)	Yes
Diode (05)	Yes
Fail-unlocked	Yes
Break-in resistance	3000 N
Height	78.7 mm
Width	21,5 mm
Depth	27.5 mm
Latch bolt engaging depth	6 mm
FaFix® adjustment range	2 mm
Max. pre-load	3000 N
Operating temperature range	-15 °C to +40 °C
Continuous function load cycles	200000
Load cycles for in-plant test	500000
Installation position	vertical and horizontal
Anchor contact	Yes
Switching capacity - monitoring contact	24 V/ 1 A
Operating voltage tolerance range	± 10%
Rated resistance	260,00 Ω
Rated current consumption	100 mA
Article number	
332.238-----F91	