



4660

POWERCOM SIMPLEBUS B/W CAMERA



Audio-video unit with terminal board complete with 1/4" CCD black and white camera which is adjustable from the front. LED camera illumination. Complete with audio speaker unit with double amplifier, watertight loudspeaker and electret microphone. Both, microphone and loudspeaker volumes, can be adjusted from the front. To be inserted in modules part. 3321/0, 3321/1 and 3321/2. Dimensions: 102x55x35 mm


4660

POWERCOM SIMPLEBUS B/W CAMERA

MAIN SPECIFICATIONS

Audio system:	No
Audio/video system:	Yes
Type of sensor:	1/4" CCD
Horizontal resolution (TVL):	350
Microphone volume control:	Yes
Loudspeaker volume control:	Yes
Operating temperature (°F):	-13 ÷ 131
S/N ratio (dB):	48
Video output:	1Vpp 75PAL

SOFTWARE/FIRMWARE SPECIFICATIONS

Video resolution (H x V):	500x582
---------------------------	---------

FUNCTIONS

Key button function:	Yes
----------------------	-----

GENERAL DATA

Product height (inches):	2.17
Product width (inches):	4.02
Product depth (inches):	1.38
S/N ratio (dB):	48

COMPATIBILITY

Simplebus 2 audio system:	Yes
---------------------------	-----

TECHNICAL SPECIFICATIONS

Sensitivity (lux):	0.5
Type of camera:	B/W

ELECTRICAL SPECIFICATIONS

Maximum current absorption (mA):	300
----------------------------------	-----



4660

POWERCOM SIMPLEBUS B/W CAMERA

ACCESSORIES



1216

VIDEO RISER TERMINATION FOR SIMPLEBUS

Line termination terminal. To be mounted at the end of the riser, according to the indications given in the technical documentation, to optimise distribution of the signals.