

DATA SHEET

COD. 4662C

POWERCOM SERIES VIP SYSTEM COLOUR AUDIO/VIDEO UNIT

Audio-video group for VIP System with terminal board complete with video camera with frontally-operated spherical colour lens and LED video camera lighting. Complete with terminal board and digital system for managing audio with Eco-cancelling, water-tight loud speaker and electret microphone, frontally adjustable loudspeaker volume. To be inserted into modules: art. 3331/0, 3331/1 and 3331/2 Dimensions: 102 x 55 x 35 mm



Compatibility

| | |
|--------------------------|-----|
| Video door entry family: | Yes |
| Vip system: | Yes |

Audio/video specifications

| | |
|------------------------------|-------------------------|
| Type of sensor: | 1/4" CCD |
| Signal/noise ratio (dB): | 48 |
| Angle of view on 3 axes (°): | D:80,27 H:67,07 V:47,37 |
| Camera pixels (H x V): | 500x582 |
| Audio/video system: | Yes |
| Video output: | 1 / 75 PAL |

Hardware specifications

| | |
|---------------|----|
| DDE function: | No |
|---------------|----|

Functions - Settings

| | |
|-----------------------------|-----|
| Key button function: | Yes |
| Loudspeaker volume control: | Yes |

Technical properties

| | |
|--------------------|----------------------------|
| Temperature range: | -25 / 55 °C |
| Sensitivity (lux): | 1,0 MAX AGC, 50% VIDEO OUT |
| Type of camera: | COLOR |

Electrical specifications

| | |
|----------------------------------|-----|
| Maximum current absorption (mA): | 400 |
|----------------------------------|-----|

General info

| | |
|-------------------|----------------|
| EAN product code: | '8023903209761 |
|-------------------|----------------|

The technical specifications are subject to variations without warning

DATA SHEET

| | |
|----------------------|----------|
| Intrastat code: | 85176920 |
| S/N ratio dB: | 48 |
| Product height (mm): | 55 |
| Product width (mm): | 102 |
| Product depth (mm): | 35 |

Packaging

| | |
|---------------------------|-------|
| Single pack height (mm): | 53 |
| Single pack width (mm): | 110 |
| Single pack weight (g): | 200 |
| Single pack depth (mm): | 94 |
| Single pack volume (dm3): | 0,548 |