



4680

SIMPLEBUS AUDIO/VIDEO UNIT WITH B/W CAMERA FOR IKALL ENTRAN.



Simplebus Color system audio/video unit with terminal block complete with front-adjustable wide-angle 1/4" B/W camera and LED camera illumination. Complete with terminal block and digital audio management system with Eco-cancelling, watertight loudspeaker and electrets microphone, loudspeaker volume can be adjusted from the front. Complete with microprocessor and DIP SWITCH with 8 positions for programming calls to users. Audiovisual indications for disabled individuals assistance request can be activated via programming. 33Vdc power supply via special power supply unit Art. 1595. On-board electronic lock-release function (3A), plus C, NC, NO contacts for 10A relay. For use in modules Art. 33410, 33411 and 33412. Dimensions: 102x55x38 mm. Compatible with all SBTOP functions and products. Allows call addressing for up to 120000 users. Timed lock-release input and door open indication.



4680

SIMPLEBUS AUDIO/VIDEO UNIT WITH B/W CAMERA FOR IKALL ENTRAN.

MAIN SPECIFICATIONS

Audio system:	No
Audio/video system:	Yes
Type of sensor:	1/4" CCD
Horizontal resolution (TVL):	350
Microphone volume control:	Yes
Loudspeaker volume control:	Yes
Operating temperature (°F):	-13 ÷ 131
S/N ratio (dB):	48
Video output:	1Vpp 75PAL

SOFTWARE/FIRMWARE SPECIFICATIONS

Video resolution (H x V):	500x582
---------------------------	---------

FUNCTIONS

Key button function:	Yes
----------------------	-----

HARDWARE SPECIFICATIONS

Visual signalling:	Yes
Acoustic signalling:	Yes

GENERAL DATA

Product height (inches):	2.17
Product width (inches):	4.09
Product depth (inches):	1.38
S/N ratio (dB):	48

COMPATIBILITY

Simplebus 2 audio system:	Yes
---------------------------	-----

TECHNICAL SPECIFICATIONS

Sensitivity (lux):	0.5
Type of camera:	B/W

ELECTRICAL SPECIFICATIONS

Maximum current absorption (mA):	400
----------------------------------	-----