

IKALL SIMPLEBUS COLOUR CAMERA

Audio/video unit with terminal block, complete with front-adjustable 1/4" colour camera and LED camera illumination. Digital audio management system with Echo-cancelling, watertight loudspeaker and electret microphone, loudspeaker volume can be adjusted from the front. Complete with microprocessor and DIP switch with 8 positions for programming calls to users. Audiovisual indications to comply with DDA via programming. 33Vdc power supply via power supply unit part. 1595. On-board electronic lock-release function (3A), plus C, NC, NO contacts for 10A relay and timed lock-release input and door open indication. For use in modules part. 33410, 33411 and 33412. Compatible with all SBTOP functions and products. Dimensions: 102x55x38 mm.



Main specifications

Simplebus Top system:	Yes
Compatible with the Building Kit System:	No
Vip system:	No
Audio system:	No
Audio/video system:	Yes
Camera:	Colors
Video encoding:	MPEG
Type of sensor:	1,3"CCD
Horizontal resolution (TVL):	540
Minimum illumination:	0,35lux
Lens size:	3,6mm
Camera orientation:	Yes
Clamps:	L L V+ V- RTE DO PR GND SE COM NC NO
Microphone volume control:	Yes
Loudspeaker volume control:	Yes
Operating temperature (°C):	-25÷55
Signal/noise ratio (dB):	48
Video output:	1Vpp 75PAL

Software/firmware specifications

Video resolution (H x V):	500x582
---------------------------	---------

Functions

Key button function:	Yes
----------------------	-----

Hardware specifications

Visual signalling:	Yes
--------------------	-----

DATA SHEET

Acoustic signalling: Yes

General info

Product height (mm): 55

Product width (mm): 104

Product depth (mm): 35

S/N ratio dB: 48

Compatibility

Simplebus Color system: Yes

Simplebus 2 system: Yes

Technical specifications

Sensitivity (lux): 1

Type of camera: Color

Packaging

Single pack height (mm): 53

Single pack width (mm): 110

Single pack weight (Kg): 0,223

Single pack depth (mm): 94

Single pack volume (dm3): 0,548