

DATA SHEET

COD. **4880**

GENIUSKIT B/W PANEL - 1 BUTTON

Flush / Surface-mounted external video entry phone (the external unit is surface mounted but a box art. 3554 is also provided to allow flush mounted installation of the external unit) with anodized aluminium facing and ample name holder slots, with LED rear-lighting. 12V AC power supply. Dimensions of external unit: 95x176x15 mm. Dimensions of flush-mounted box: 95,5x176x5x35 mm.



Main specifications

Backlighting colour:	LED BLUE
Vandal Resistant IK:	No

Compatibility

Simplebus 2 system:	SI
---------------------	----

Mounting/Installation

Flush-mounted:	SI
Wall-mounted:	SI
Surface-mounted:	SI

Audio/video specifications

Type of sensor:	1/3" CCD
Signal/noise ratio (dB):	45
Angle of view on 3 axes (°):	D:80,27 H:67,07 V:47,37
Camera pixels (H x V):	500x582
Horizontal resolution (TVL):	350
Audio system:	No
Audio/video system:	SI
Video output:	1 / 75 PAL

Hardware specifications

Customisable housing:	No
DDE function:	No
Total buttons:	1
Sensitive Touch technology:	No

DATA SHEET

Functions - Settings

Key button function:	SI
Loudspeaker volume control:	SI
Microphone volume control:	SI

Technical properties

Temperature range (°C):	-25/55
Sensitivity (lux):	0,1
Type of camera:	B/W

Electrical specifications

Maximum current absorption (mA):	300
----------------------------------	-----

General info

EAN product code:	8023903179057
Intrastat code:	85176990
S/N ratio dB:	45
Product height (mm):	176
Product width (mm):	95
Product depth (mm):	15
Product colour:	GREY

Packaging

Single pack height (mm):	170
Single pack width (mm):	100
Single pack weight (g):	350
Single pack depth (mm):	70
Single pack volume (dm3):	1,19