## DATA SHEET

# COD. 6202W/C

#### PLANUX WHITE LUX VIP MONITOR

3.5" color display with On-Screen Display and a glass fascia. Features sensitive touch technology, hands-free function and audio, ringtone, color and contrast controls. Ringtones can be customised, selecting from the variety of polyphonic tones provided. Full-duplex voice function. Monitor with SD card slot. Memovideo function and internal directory for intercom call management. To be completed with backplate art. 6231. Dimensions 160x167x14mm.



#### Compatibility

Video door entry family:	SI
Vip system:	SI

#### Mounting/Installation

Flush-mounted:	SI
Wall-mounted:	No
Desk base-mounted:	No
Surface-mounted:	SI

#### Audio/video specifications

B/W or colour display:	COLOR
OSD display:	SI
Touch screen display:	No
On-screen display (OSD):	SI
Display resolution (H x V):	320x240 PIXEL
Audio system:	No
Audio/video system:	SI

#### Hardware specifications

Additional buttons:	No	
Total buttons:	10	
SD memory card:	SI	
Sensitive Touch technology:	SI	

#### Software/firmware specifications

IP assignment:

ATUO IP



The technical specifications are subject to variations without warning

## **DATA SHEET**

### Connectivity

Type of connections/ports:	ETHERNET	

## **Functions - Settings**

unctions - Settings	
Automatic gain control (AGC):	SI
Alarm function:	SI
Switchboard call function:	SI
Floor door call function:	SI
Actuator control function:	YRS
Privacy conversation function:	SI
Induction loop function:	SI
Intercom function:	SI
Privacy function:	SI
Key button function:	SI
Hands-free function:	SI
Full Duplex hands-free function:	SI
Display colour control:	SI
Display contrast control:	SI
Display brightness control:	SI
Loudspeaker volume control:	SI
Microphone volume control:	No
Ringtone volume control:	SI
echnical properties Temperature range (°C):	-5/55
Temperature range (°C):	-5/55
Temperature range (°C):	
Temperature range (°C):	-5/55 150
Temperature range (°C):	
Temperature range (°C):  Electrical specifications  Maximum current absorption (mA):  Beneral info	
Temperature range (°C):  Electrical specifications  Maximum current absorption (mA):  General info  Self-ignition:	150
Temperature range (°C):  Electrical specifications  Maximum current absorption (mA):  Electrical info  Self-ignition: EAN product code:	150 SI 8023903245912
Temperature range (°C):  Electrical specifications  Maximum current absorption (mA):  General info  Self-ignition:	150 SI
Temperature range (°C):  Electrical specifications  Maximum current absorption (mA):  Elemeral info  Self-ignition: EAN product code: Intrastat code:	150 SI 8023903245912 85176910
Temperature range (°C): Electrical specifications Maximum current absorption (mA): Elemeral info Self-ignition: EAN product code: Intrastat code: Customisable ringtone: Product height (mm):	150 SI 8023903245912 85176910 SI
Temperature range (°C):         Electrical specifications         Maximum current absorption (mA):         General info         Self-ignition:         EAN product code:         Intrastat code:         Customisable ringtone:         Product height (mm):         Product width (mm):	150 SI 8023903245912 85176910 SI 167 169
Temperature range (°C): Electrical specifications Maximum current absorption (mA): Elemeral info Self-ignition: EAN product code: Intrastat code: Customisable ringtone: Product height (mm):	150 SI 8023903245912 85176910 SI 167
Temperature range (°C):         Electrical specifications         Maximum current absorption (mA):         Seneral info         Self-ignition:         EAN product code:         Intrastat code:         Customisable ringtone:         Product height (mm):         Product depth (mm):         Product depth (mm):	150 SI 8023903245912 85176910 SI 167 169 38
Temperature range (°C):         Electrical specifications         Maximum current absorption (mA):         Seneral info         Self-ignition:         EAN product code:         Intrastat code:         Customisable ringtone:         Product height (mm):         Product depth (mm):         Product depth (mm):	150 SI 8023903245912 85176910 SI 167 169 38
Temperature range (°C):         Electrical specifications         Maximum current absorption (mA):         General info         Self-ignition:         EAN product code:         Intrastat code:         Customisable ringtone:         Product height (mm):         Product width (mm):         Product weight:	150 SI 8023903245912 85176910 SI 167 169 38



The technical specifications are subject to variations without warning

# DATA SHEET

Single pack weight (g):	875	
Single pack depth (mm):	204	
Single pack volume (dm3):	3,26	

