

VIDEOINTERCOM KIT 637E

Surface Mount Entry Panel



Kit includes:

- 88V1** Surface Mount 1 Button Entry Panel with Camera, Speaker and Microphone
- 637K** Videointercom Station
- 832/030** Transformer

Packaged in carton with carry handle

Description

The Elvox 637E kit contains everything required to install a complete 1-1 videointercom system including:

- * A Galileo Style surface mount entry panel containing an integral high resolution, pivoting camera with IR illumination and a crystal clear speaker/mic.
- * A hi resolution videointercom monitor station with handset.
- * Power transformer.

Operation

Automatic visitor activation as well as self-activation from the monitor station. Door release is standard and requires no additional wiring. The door release is wired to nearby entry station, not inside station.

Options

- | | |
|---------------------------|---------------------------------------|
| 2nd videointercom monitor | Extension handset station |
| Chime extension | ADA strobe kit |
| Desk kit | Special application mounting hardware |

Info

The Elvox 637 systems utilized standard video signals allowing easy integration into other CCTV accessories such as VCR's, multiplexers, quads, etc

Specifications

Entry Panel:

- Dimensions: 4" W x 6" H x 1.25" D
- Construction: Extruded Aluminum
Stainless Steel pushbutton
LED Backlit Name Tab
- Mounting: Surface
- Hardware: Tamperproof screw (Tool provided)

Camera:

- CCD Size: Pinhole on pivoting head
- Resolution: 625 lines Horizontal
- Illuminator: 6 LED Infrared

Speaker/Mic:

- 8 ohm speaker/electret microphone.

Monitor:

- Screen: 4" High Brightness, Hi resolution
- Controls: Door Release, Auto Turn on, Brightness, Ring level, Auxilliary

Transformer:

- 15VAC, 30 VA

Cable required:

- Coax + 2c