


7" MAXI SERIES MONITOR. SBC SYSTEM

Colour monitor for flush-mounting (on Art. 6817) or wall-mounting (on support Art. 6820) with 7" 16:9 screen, hands-free full-duplex audio and touch sensitive controls. Allows brightness, contrast and audio volume control, plus adjustment of the ringtone, which can be customised with a choice of different melodies. Equipped as standard with control buttons for lock-release and audio enable/disable with relative indicator LEDs, plus 6 further buttons for self-ignition, privacy service and other programmable functions. Manages floor door calls and call repeat as standard. Complete with 2 x 8-position DIP-switches for user code programming and button programming. Equipped with riser distribution terminal Art 1214/2C. The monitor can only be used in 2-wire SimplebusTop Color systems. Dimensions: 223x124x25mm.



Main specifications

System:	SBT S2(2-wires)
Audio/video system:	Yes
Flush-mounted:	Yes
Wall-mounted:	Yes
Desk base-mounted:	Yes
Hands-free function:	Yes
Type of display:	LCD
Display size (inches):	7" 16/9
Display resolution (H x V):	800x480pixel
B/W or colour display:	Color
Product colour:	White
Buttons with technology cap sense:	Yes
Sensitive Touch technology:	Yes
Total buttons:	14
LED signaling:	14
Backlighting color:	White

Functions

Actuator control function:	Yes
Self-ignition:	Yes
Switchboard call function:	Yes
Intercom function:	Yes
Privacy function:	Yes
Redial:	Yes
Floor door call function:	Yes
Customisable ringtone:	Yes

DATA SHEET

Alarm function:	Yes
Privacy conversation function:	Yes
Key button function:	Yes
Full Duplex hands-free function:	Yes

Hardware specifications

Removable terminals:	Yes
----------------------	-----

Settings

Loudspeaker volume control:	Yes
Microphone volume control:	Yes
Ringtone volume control:	Yes
Display brightness control:	Yes
Display contrast control:	Yes

General info

Product height (mm):	124
Product width (mm):	223
Product depth (mm):	25

Compatibility

Video door entry family:	Yes
Simplebus Top system:	Yes
Simplebus Color system:	Yes

Technical specifications

Power supply voltage:	22÷28Vdc
Maximum current absorption (mA):	400
Power consumption stand-by (mA):	36
In called absorption (mA):	310
In communication absorption (mA):	400
Microphone:	5mm omni-direction
Loudspeaker:	80mm 80Ohm 1W
IP Rating:	30
Operating temperature (°C):	-5÷40
Video encoding:	MPEG
Product weight (g):	0,7
Clamps:	CFP1 CFP2 IN1 IN2 S+ S-

Packaging

Single pack height (mm):	70
Single pack width (mm):	159
Single pack depth (mm):	259

DATA SHEET

Single pack volume (dm3):

2,88