

6502/G2+ coded panel



Reference: 6502/G2+
Product code: 12226502A
EAN code: 8429898022000



Main characteristics

- Coded panel with G2+ technology of two non-polarised wires.
- Vandal resistant (IK-07) and weatherproof (IP-65) panel made of 5mm thickness anodized aluminium.
- 2MPx HD 120° wide angle camera with white self-starting LEDs for night vision.
- 4.3" panoramic TFT LCD colour screen with 480x272px resolution.
- Inductive loop antenna for the heard impairment people.
- Presence sensor and ambient light sensor.
- Backlit metal buttons with silk-screen printing of numbers.
- Acoustic confirmation tones when buttons are pressed.
- Coded keyboard that allows two calling methods: introduction of the code of the house to call or by search in the phonebook.
- RFID proximity reader for up to 2000 cards. 13,56 MHz cards are accepted.
- RJ-45 connector for programming.

Promotional video of the 6502/G2+ door panel.

Dimensions: 155(W) x 318(H) x 5(D)mm.

More information

- The panels include Wiegand 26 (input/output) as standard:
 - **Input:** allows the connection of an external reader; the panel validates proximity and PIN.
 - **Output:** the panel acts as a reader, sending proximity and PIN identifications to Wiegand controllers (WCONTROL or iP-OPENER).**In versions with a 2SAFE antenna, proximity must be managed using iP-Opener 2SAFE or EASYGATE controllers.*
- CCTV input for an analogic camera.
- Possibility of displaying the door panel images in its own screen in a communication process.
- Basic programming via the menu in the screen and advanced settings through the web client.
- Remote programming through the "Sixty5 cloud" website.
- Daily back-up in microSD card.
- Anti-sabotage alarm tamper.
- 12 Vcc input for local power.
- 2 relay contacts and 2 exit push button inputs.
- Requires a CE-6502 SE embedding box.

Accessories

- 6502/INFO informative panel
- KEYPROX SE proximity fob
- CE-6502 TE embedding box for Sixty 5 door panels
- S7165 SE surface box with integrated rain shield
- 13,56MHz NFC/US user proximity card
- ISOPROX proximity card
- MAC-6502 adapter frame
- UC-6502 CABLE TUNNELS SET
- S7865 SE rain shield Sixty 5
- 13.56MHz TAGNFC/US proximity keyfob

Visit in the website: <https://www.golmar.es/products/6502-g2-plus>

Visit in the website: <https://www.golmar.es/products/6502-g2-plus>