



8521

IKALL METAL AND ICONA KIT.VIP H264 SYSTEM

The kit consists of 1 colour audio/video unit art. 4682HKC, 1 module with 1 button art. 33411M, 1 flush-mounted box art. 3110/1, 1 frame complete with finishing frame art. 3311/1S, 1 power supply unit art. 1595, 1 power supply unit art. 1441B, 1 switch art. 1440, 1 Icona monitor art. 6602WK, 1 flush-mounted box art. 6117, 1 wall-mounted bracket art. 6620. The kit is pre-programmed and ready to use. The kit can be expanded with other products from the VIP catalogue. Compatible with H.264 video format.



8521

IKALL METAL AND ICONA KIT.VIP H264 SYSTEM

MAIN FEATURES

Single Family:	Yes
N° external units:	1
External units:	Art. Ikall Metal
N° internal units:	1
Internal units:	Icona



8521

IKALL METAL AND ICONA KIT.VIP H264 SYSTEM

ACCESSORIES



1441B

30W VIP SYSTEM POWER SUPPLY UNIT

Power supply unit with 110Vac/240Vac input and 48Vdc output. 30W power. DIN bar power supply unit (4 DIN modules). Dimensions: 72x93x56mm



4894HIM

External unit for VIP kit - Ikall Metal H264

Single-family video door entry external unit for ViP system with Ikall Metal entrance panel. The kit comprises: 1 flush-mounted box Art. 3110/1, 1 silver coloured frame Art. 3311/1S, 1 module with 1 button art. 33411M and 1 colour audio/video unit Art. 4682HKC. The external unit is coded with ViP address 100 and the button on module Art. 33411M sends the call to ViP address 1. Compatible with H264 video format



6602WK

ICONA MONITOR, VIP KIT H264

Flush-mounted (on box art. 6117) or surface-mounted (with bracket art. 6620) colour monitor with 4.3" / 16:9 touch screen, full-duplex audio. Allows adjustment of backlighting intensity, contrast, audio volume and ringtone volume. Equipped as standard with sensitive touch controls for lock-release, audio activation, self-ignition, privacy service and 3 other controls for programmable functions, door open and new message indicator LEDs. Standard floor door call and call repetition management, with alarm and panic inputs and micro-SD card slot. You can customise the ringtone and video memory function with an absent message. Can also be used on standard PoE systems. Dimensions 5.61"x5.79"x0.91". Compatible with H.264 video format.



6620

WALL BRACKET FOR ICONA MONITOR

Wall bracket for Icona monitor. Colour: White. Dimensions: 137X142X12.5 mm.



1440

NETWORK SWITCH 4 PORT

PoE Ethernet switch with 2 ports (10/100 Mb) and 4 ports (10 MB). Dimensions 66 x 85 x 35 mm



8521

IKALL METAL AND ICONA KIT.VIP H264 SYSTEM

ACCESSORIES



6117

PLANUX, SMART, ICONA FLUSH BACKBOX

Flush mounted box for Planux, Smart and Icona monitors Dimensions: 132x132x50mm



1595

33VDC POWER SUPPLY UNIT FOR IKALL ENTRANCE PANEL

Power supply unit 110-230V input and 33Vdc 500 mA continuous output, and 1.2A inrush current for external unit with IKALL entrance panel. Equipped with internal protection against overcurrent and short circuits. Dimensions: 71.7x90x62 mm (4 DIN modules).