



8531

IKALL METAL AND ICONA KIT, GATEWAY SLAVE. H264

The kit consists of 1 VIP kit external panel 4894HIM, 1 power supply unit art. 1595, 1 power supply unit art. 1441B, 1 slave gateway art. 1456S, 1 Icona monitor art. 6602WK, 1 flush-mounted box art. 6117, 1 wall-mounted bracket art. 6620. The kit is pre-programmed and ready to use, except for 1456S gateway configuration which must be carried out via internal web server. The kit can be expanded with other products from the VIP catalogue. Compatible with H.264 video format.



8531

IKALL METAL AND ICONA KIT, GATEWAY SLAVE. H264

MAIN FEATURES

Single Family:	Yes
N° external units:	1
External units:	Art. Ikall Metal
N° internal units:	1
Internal units:	Icona



8531

IKALL METAL AND ICONA KIT, GATEWAY SLAVE. H264

ACCESSORIES



1441B

30W VIP SYSTEM POWER SUPPLY UNIT

Power supply unit with 110Vac/240Vac input and 48Vdc output. 30W power. DIN bar power supply unit (4 DIN modules). Dimensions: 72x93x56mm



1456S

APARTMENT SLAVE GATEWAY FOR VIP SYSTEM

Apartment gateway in slave version (requires presence of a door entry monitor). Allows the operation of door entry monitor system via tablets and smartphones using the Comelit ViP App, which can be downloaded free of charge. This function can be used locally via a Wi-Fi network or on portable devices using 3G (or higher) networks; automatic switching between Wi-Fi and 3G networks according to availability. In all cases, the gateway should be connected to an ASDL router or another device guaranteeing local Wi-Fi and mobile 3G connectivity. Depending on bandwidth limitations, the gateway can serve up to 15 appliances (including door entry monitors, smartphones, tablets and PCs) with 4 simultaneous audio/video streams. It also allows "intercom" communication between all of the 15 devices served. The gateway is equipped with 1 Ethernet port for ViP system riser input, 1 PoE port, 2 PoE ports (can be set to non-PoE) and 1 non-PoE port. It is also equipped with an input for the power supply. Dimensions: 70x90x62 mm (4 DIN modules).



4894HIM

External unit for ViP kit - Ikall Metal H264

Single-family video door entry external unit for ViP system with Ikall Metal entrance panel. The kit comprises: 1 flush-mounted box Art. 3110/1, 1 silver coloured frame Art. 3311/1S, 1 module with 1 button art. 33411M and 1 colour audio/video unit Art. 4682HKC. The external unit is coded with ViP address 100 and the button on module Art. 33411M sends the call to ViP address 1. Compatible with H264 video format



6602WK

ICONA MONITOR, VIP KIT H264

Flush-mounted (on box art. 6117) or surface-mounted (with bracket art. 6620) colour monitor with 4.3" / 16:9 touch screen, full-duplex audio. Allows adjustment of backlighting intensity, contrast, audio volume and ringtone volume. Equipped as standard with sensitive touch controls for lock-release, audio activation, self-ignition, privacy service and 3 other controls for programmable functions, door open and new message indicator LEDs. Standard floor door call and call repetition management, with alarm and panic inputs and micro-SD card slot. You can customise the ringtone and video memory function with an absent message. Can also be used on standard PoE systems. Dimensions 5.61"x5.79"x0.91". Compatible with H.264 video format.



8531

IKALL METAL AND ICONA KIT, GATEWAY SLAVE. H264

ACCESSORIES



6620

WALL BRACKET FOR ICONA MONITOR

Wall bracket for Icona monitor. Colour: White. Dimensions: 137X142X12.5 mm.



6117

PLANUX, SMART, ICONA FLUSH BACKBOX

Flush mounted box for Planux, Smart and Icona monitors Dimensions: 132x132x50mm



1595

33VDC POWER SUPPLY UNIT FOR IKALL ENTRANCE PANEL

Power supply unit 110-230V input and 33Vdc 500 mA continuous output, and 1.2A inrush current for external unit with IKALL entrance panel. Equipped with internal protection against overcurrent and short circuits. Dimensions: 71.7x90x62 mm (4 DIN modules).