

PAC GS3 Range

Reader—MT

909020115 – PAC MT Admin Reader

PAC's Multi-tech Administration Reader is used for adding credentials in to PAC software, including cloud-based and stand-alone systems.



- USB cable and software drivers included
- Reads all PAC credentials for OPS, OPS Lite, PAC, KeyPAC
- 3rd party external reader can be connected (see install guide for details)

Part Number(s)	909020115 – PAC MT Admin Reader
Supported Credential Formats	OPS, OPS Lite, PAC, KeyPAC, Wiegand Prox
Output Formats	PAC64, PAC
Audio / Visual Indicators	Red/Green LEDs
RFid Frequency	HF 13.56MHz LF 125kHz and 153kHz
Maximum Read Range	100 mm / 4 in.
Recommended Cabling	USB lead supplied A 3rd party external reader can be wired into the screw terminals when the base cover of the Admin reader is removed. Full details available in install guide.
Power input(s)	USB powered.
Dimensions	88 (w) x 130 (h) x 29 (d) mm / 3.45 (w) x 5.12 (h) x 1.15 (d) in.
Weight	0.230 kg / 0 lb 8 oz.
Material	UL rated Polycarbonate
Operating Temperature	-40°C to +66°C / -40°F to 151°F
Operating Humidity	10% to 85% Relative Humidity
Warranty	1 year against electronic failure
Standards Compliance	UL, FCC, IC, UKCA, CE, WEEE, EN 50131
Environment	Indoor only
Country of Origin	Albania