



AHDVR004S08ASL

XVR 4 INPUTS 4K, NO HDD



5-hybrid stand-alone digital video recorder (AHD/TVI/CVI/CVBS/IP), 4 analogue video inputs or 2 analogue video inputs and 7 IP video inputs or 16 IP video inputs.



AHDVR004S08ASL

XVR 4 INPUTS 4K, NO HDD

MAIN FEATURES

Video inputs	4 BNC / 16 IP (4K max) / 2 BNC+7 IP (4K max)
Main video output	1 (HDMI), 1 (VGA)
Audio Inputs/Outputs	4 (RCA) / 1 (RCA), G.711u, 64 kbps
Video compression	H.264 / H.264+ / H.265 / H.265+ (128÷8192 kbps)
Playback / recording frame rate	BNC: 4 (4K@8fps, 5MP@12fps, 4MP@15fps, 3MP@18fps, 2MP@25fps, HD@25fps). IP: 8 (4K), 12 (5MP), 16 (4MP, 3MP, 2MP, HD) @25fps
Additional Hard Disks (SATA)	1 (8TB max)

SOFTWARE/FIRMWARE SPECIFICATIONS

Operating system	Linux embedded
Recording methods	Auto, manual, scheduled, motion
Recording type	Dual streaming
Maximum number of channels being played simultaneously	BNC: 4 (4K@8fps, 5MP@12fps, 4MP@15fps, 3MP@18fps, 2MP@25fps). MIX: 1 (4K@30fps), 2 (5MP@30fps), 3 (5MP@12fps, 3MP@18fps), 4 (2MP@30fps). IP: 1 (4K@30fps), 2 (5MP, 4MP@30fps), 3 (3MP@30fps), 4 (2MP, HD@30fps)
Protocols supported	DDNS, Comelit DNS, DHCP, FTP, HTTP, NTP, PPPoE, RTCP, RTP, RTSP, SMTP, UPnP, TCP/IP IPv4
IP assignment	DHCP, manual
Encrypted transmission	SSL
Max bandwidth (Mbps)	80
Remote control via browser	Internet Explorer
Remote control by software	Comelit View Smart
Remote control by mobile	app Comelit View Smart (Android, iOS)
Users connected at the same time	3
Main functions	Camera control through coax cable via UTC protocol, Watermarking function, OSD menu multilanguage, Instant playback function

FUNCTIONS

Motion detection (zones)	396
--------------------------	-----



AHDVR004S08ASL

XVR 4 INPUTS 4K, NO HDD

FUNCTIONS

Privacy zones (n°)	3
Loss of video signal	Yes
PTZ management by RS485 (Pelco-P, Pelco-D protocols)	Yes (Pelco-P, Pelco-D)
Digital effects	E-zoom
Remote system log	Yes
E-mail notification	Yes
Pre-event recording	5 ÷ 30 seconds

HARDWARE SPECIFICATIONS

Type of connections/ports	1xEthernet 10/100 Mbit/s, 2xUSB 2.0, 1xRS485
---------------------------	--

GENERAL DATA

Max absorption (W)	17
Power supply voltage	12
Supply voltage	100 ÷ 240, 50 ÷ 60Hz
Height (mm)	43
Width (mm)	215
Depth (mm)	260
Product weight (g)	2500
Type of finishing materials	Metallic
Product color	Black
Operating temperature (°C)	-10 ÷ 55
Operating humidity (RH max) (%)	25 ÷ 90
Supplied accessories	Power supply, Mouse
System backup	USB 2.0