

CDV91-SF & CDV92-SF

This standard 1-way door station is available with either 1 or 2 buttons.

Part of the 2Easy range, this colour outdoor station with wide angle camera is available in surface versions (CDV91 & CDV92)

The modern low profile styling suits all environments and is compatible with all of the 2Easy range.



Overview

- Stainless steel panel
- High resolution camera
- 105° visual angle
- Auto-sensor light illumination
- Flush mounting



The 2EASY system from CDVI offer convenient and high quality video entry. Connection throughout is 2-wire, non polarised providing simple and efficient installation and maintenance.

CDV91-SF&92-SF - Technical Specifications

Product Specifications

Material: Stainless steel panel
Flush mount
Unlocking time: 1 to 30s (default 1s)

Camera

Colour ARS, 650TVL
1/4" camera, 150° wide angle

Output Specifications

Number of relay circuits: 2*
*the second lock output requires CDV-RLC

Electrical Specifications

Power Supply: 24Vdc
Power Consumption: standby 33mA, working 110mA
Lock Power Supply: 12Vdc, 250mA (Internal power - Fail secure only)

Wiring

2-wire
No polarity

Dimensions

Dimensions: 188 x 110 x 39mm (front panel) - 117 x 91 x 40mm (back box)
Environment: -15°C to 55°C