



**3006/N**

## FLUSH-MOUNTING 'N' SERIES SINGLE-PLATE ENTRANCE PANELS



Entrance panels made of 4 mm thick anodized aluminium, 16 mm diameter aluminium push-buttons, extruded aluminium impact-proof grill, galvanized sheet flush-mounting box. Self-adjusting and independent button assembly. All the entrance panels are fitted with bulb holder (without bulb) for Ø 6.3 x 39 mm festoon bulbs. The flush-mounting 'N' entrance panels can be converted into surface-mounting or gate-mounting types using P or S type housings. To be completed with audio speaker unit Art. 1102 for systems with traditional cabling or with audio speaker unit Art. 1103 for systems with simplified cabling. In this system the entrance panel is also to be complete with a diode module Art. 1134 for each push-button. Push-buttons: 6 Rows of push-buttons: 1 Front dimensions: 100x362 mm Box dimensions: 90x351x55 mm



**3006/N**

# **FLUSH-MOUNTING 'N' SERIES SINGLE-PLATE ENTRANCE PANELS**



**3006/N**

## FLUSH-MOUNTING 'N' SERIES SINGLE-PLATE ENTRANCE PANELS



### **3006/S HOUSING FOR 'N' TYPE SINGLE-PLATE ENTRANCE PANELS**

Watertight aluminium housings, for assembly on gate. Entrance panel: 3006/N Dimensions: 105x372x100 mm



### **3006/P HOUSINGS FOR 'N' TYPE SINGLE-PLATE ENTRANCE PANELS**

Watertight aluminium housings, for assembly on wall. Entrance panel: 3006/N Dimensions: 105x372x64



### **1602VC POWERCOM REMOTE COLOUR CAMERA AUDIO UNIT SB2**

Module which allows modulation and transmission of the video signal on the riser. On input it has the composite video signal of a B/W camera. Power supply: 12V AC. Dimensions: 102X55X35 mm. From the RI002 it is compatible with all Simplebus 2 functions and products. It allows call addressing for up to 120000 users.



### **1602 POWERCOM AUDIO UNIT. SB1**

Audio speaker unit for Simplebus system with terminal board and double amplifier, watertight loudspeaker and electret microphone, Both, microphone and loudspeaker volumes, can be adjusted from the front. Complete with microprocessor and DIP SWITCH with 8 positions for programming the calls to the users. 12 V AC power supply (use Art. 1395/A). Electronic door-opening function on board (3A). To be inserted in modules Art. 3320/0, 3320/1 and 3320/2. Dimensions: 102X55X35 mm. From the RI27 it is compatible with all Simplebus 2 functions and products. It allows call addressing for up to 120000 users.



### **1250 A/V AND AUDIO UNIT FOR SINGLE PLATE**

Accessory which allows audio speaker units Art.1600, 1601 and 1602 to be mounted and used on N and AV/4 series entrance panels



---

**3006/N**

## **FLUSH-MOUNTING 'N' SERIES SINGLE-PLATE ENTRANCE PANELS**



**1172**

**VANDALCOM 12/24V BULBS**

24V/3W festoon bulb for illuminating name labels.