

**3061MU****MASTER BUTTON WITH NAMEPLATE. EU GROUPS**

Master button that can be used in Simplebus 1, Simplebus 2 and ViP systems. For use in systems with EU series units. UDB communication protocol. Consists of a nameplate holder and a mechanical button in stainless steel. The brightness level of the white LED can be adjusted on the back. Up to 3 slave buttons art. 3061S can be connected using the cable supplied. Installation should take place on 2.5 mm thick metal front plates.



**3061MU**

**MASTER BUTTON WITH NAMEPLATE. EU GROUPS**

**GENERAL DATA**

Height (mm)	25
Width (mm)	90
Depth (mm)	25
Flush-mounted	Yes

**COMPATIBLE SYSTEMS**

Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Audio Simplebus 2 with power supply art. 1210/1210A	Yes
Audio Simplebus 1	Yes
ViP	Yes

**ELECTRICAL CHARACTERISTICS**

Absorption in stand-by (W)	0.03
Maximum absorption (W)	0.11

**HARDWARE FEATURES**

Call type	Push-buttons
Type of buttons	Mechanical
Backlight colour	White

**SETTINGS**

Backlight brightness	Yes
----------------------	-----

**PROGRAMMING MODE**

ViP Manager software	Yes
----------------------	-----

**ENVIRONMENTAL AND COMPLIANCE FEATURES**

Operating temperature (°C)	-25 ÷ 55
----------------------------	----------



**3061MU**

## MASTER BUTTON WITH NAMEPLATE. EU GROUPS

### ENVIRONMENTAL AND COMPLIANCE FEATURES

Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	IV
Certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)