



---

**DEC0804**

**8MP DECODER, 4 OUT HDMI**



---

4K HDMI decoder, 4 HDMI video outputs, device used to create video wall and picture-in-picture multiscreen displays. Integration with Comelit VMS.



**DEC0804**

**8MP DECODER, 4 OUT HDMI**

**MAIN FEATURES**

Video inputs	1 x HDMI (FULL-HD max)
Video output	4 x HDMI (4K max), 4 x VGA (FULL-HD max), 4 x CVBS

**SOFTWARE/FIRMWARE SPECIFICATIONS**

Video compression	H.264, H.265
Frame rate	50fps
Operating system	Linux embedded
Decoding capability	8CH 8MP/5MP@30fps or 16CH 4MP/3MP or 32CH 1080P@30fps or 64CH 720P@30fps or 128CH D1 or lower @30fps

**HARDWARE SPECIFICATIONS**

Audio Inputs/Outputs	1 / 1 (jack, 2Vpp, 1Kohm) + 4 (RCA)
Type of connections/ports	1xUSB 2.0, 1xUSB 3.0, 2xEthernet 10/100/1000 Mbit/s

**GENERAL DATA**

Supply voltage	12VDC
Width (mm)	380
Depth (mm)	268
Product weight (g)	2000
Type of finishing materials	Metallic
Product color	Black
Operating temperature (°C)	-20 ÷ 50
Operating humidity (RH max) (%)	5 ÷ 90