

**HUB32LCD****32 ZONE RADIO CONTROL PANEL, LCD INTERFACE, IP**

The Secur HUB wireless intruder alarm control panel can be used to monitor up to 32 wireless zones. The total number of zones can rise to 96 if the magnetic contact auxiliary inputs are used. HUB32LCD offers integrated Wi-Fi and LAN interfaces, optional 2G and 3G modules, programming via USB, LAN and Cloud. It can manage up to 32 different users and 32 two-way radio controls. The control panel comes with two backplates: one flush-mounted and one raised to allow side entry of the wires. An optional desk base provides even greater positioning flexibility. HUB32LCD has a Capsense keypad with backlighting that can be fully switched off when the system is in standby. A built-in speaker and microphone offer two-way audio communication between a telephone and the monitored rooms. Two outputs and two wired inputs are built in and available directly on the backplate.

AWARDSDESIGN
MILANODESIGN PLUS
powered by light building


HUB32LCD
32 ZONE RADIO CONTROL PANEL, LCD INTERFACE, IP
MAIN FEATURES

Wireless technology	Bidirectional - BeaconPlus
Frequency band (n°)	868.05 ÷ 869.95
Range (meters open field) (m)	1500
No. of managed radio zones (n°)	32
No. of managed wired zones (n°)	2
Radio outputs (n°)	32
Wired outputs	2
Sensors supervision	Yes, adjustable
Number of radio controls (n°)	32
User codes (n°)	32
Installer codes (n°)	2
Display	LCD 16 x 2 characters
Video verification	Yes
Set mode	Total, Partial 1, Partial 2
Timer (secs)	16
Setting programs (n°)	16
Macro (n°)	10
Keypad technology	CapSense
Tamper	Anti-tamper and anti-tear
Live cameras	16 (viewing from Comelit App) @ 5fps, 384 kbps, HD
IP camera recording	4 @ 5fps, 384 kbps, HD
Indoor siren	Integrated speaker (2W)

COMMUNICATION

TCP-IP channel	Yes
Port programming	Mini USB, TCP (LAN) RJ45
Reporting protocols	Voice, SMS, email, CID, SIA, SIA IP, CID IP, SIA SMS, CID SMS, APP
Voice guide	Yes, local


HUB32LCD
32 ZONE RADIO CONTROL PANEL, LCD INTERFACE, IP
COMMUNICATION

GSM/GPRS/3G channel	2G or 3G module
SIM card	Micro-SIM (not included)
Wi-Fi	Integrated
"Access point" function	Yes
Two-directional audio	Yes
Voice menu	Yes
Audio module	Yes
Customisable audio events	Yes

SOFTWARE/FIRMWARE SPECIFICATIONS

APP	Comelit (iOS, Android)
Software	HUB manager (Windows)
Wizard installation on board	Yes
Maximum number of apps	8

HARDWARE SPECIFICATIONS

Dimensions (W x H x D)	150 x 230 x 31mm
Weight battery included (kg)	0.63
Operating temperature (°C)	-10 ÷ 40
Support backplates	Wall mounting (integrated terminal block), table base (optional)
Additional backplate for side entry of wires	Yes, included
Vandal Resistant rating (IK code)	IK06

ELECTRICAL SPECIFICATIONS

Auxiliary power outputs on board	1
Power output characteristics on board	13.8VDC / 50mA
Battery included	3.6VDC / 4250 mAh
Wired output features	Open Collector, 12VDC / 100mA



HUB32LCD

32 ZONE RADIO CONTROL PANEL, LCD INTERFACE, IP

ELECTRICAL SPECIFICATIONS

Power supply	90÷240VAC / 50÷60Hz
--------------	---------------------



HUB32LCD

32 ZONE RADIO CONTROL PANEL, LCD INTERFACE, IP

ACCESSORIES



HUBDESK **DESKTOP BASE FOR HUB CONTROL PANELS**

The HUBDESK backplate allows the HUB32LCD alarm control panel to be fitted on a horizontal support such as a shelf or table. The power cable is not included.