

**IPTCAMA04FB****IP TURRET CAMERA 4MP 2.8MM****ADVANCE**
SERIE

'Advance series IP turret camera, 2.8 mm fixed lens, resolution 4MP@30 fps, High frame rate function supported (2MP@60 fps). IR LEDs with a range of 30 metres (Smart IR), ONVIF compatible (Profile S and Profile G). The high frame function (60fps) is only supported by 32/64/128 ch Advance series NVRs. Video analysis functions: Scene change detection, Object abandoned/removed function, heat map, Face detection, Video tamper detection, Line cross detection (distinction between humans / vehicles), Detection of Entry into / Exit from / Intrusion into an area (distinction between humans / vehicles), Human / vehicle counting on a line and in an area. WDR 120 dB, compression H.265+/H.265/H.264+/H.264/MJPEG, SD slot (max. 256 GB). Audio: 1 in, built-in microphone. Die-cast aluminium IP67 waterproof enclosure, power supply 12 VDC/ PoE IEEE802.3af. Compatible with browsers: IE/Google Chrome/Edge/Firefox/Safari. Compatible accessories: JBA-TBBA, CMA-KTBBA, WMA-KTBBA, PMA-A, AMA-A, WMA-01A.

AWARDS



IPTCAMA04FB

IP TURRET CAMERA 4MP 2.8MM

MAIN FEATURES

Camera sensor	1/3" CMOS
Lens optical dimensions (mm)	2.8
Horizontal FoV (°)	95
Vertical FoV (°)	53
Diagonal FoV (°)	115.2
Electronic shutter (s)	1/25 ÷ 100000
Sensitivity	0.005 (colour), 0 (B/W, led IR ON)
Signal/noise ratio (dB)	>50 (AGC OFF)
IR filter	Mechanical
Video trasmission	Triple streaming
Management software	Comelit CCTV Manager
Video resolution	2592x1520 (4MP)

SOFTWARE/FIRMWARE SPECIFICATIONS

Video compression	H.264 / H.264+ / H.265 / H.265+
Frame rate	30/60fps
Protocols supported	DDNS, Comelit DNS, DHCP, FTP, HTTP, HTTPS, IPv4, IPv6, NTP, PPPoE, QoS, RTSP, SMTP, UDP, UPnP, SNMP, IEEE 802.1x, ONVIF - (Profile-S, Profile-G), RTMP
Updating firmware using network	Yes
Users connected at the same time	10 (live)
Network security	Multi-user authorization, HTTPS, AES encryption, RTSP verif.
Remote viewer from browser	Edge, Firefox, Chrome, Safari
Remote control by mobile	APP Comelit CCTV

FUNCTIONS

Motion detection	396
------------------	-----



IPTCAMA04FB

IP TURRET CAMERA 4MP 2.8MM

FUNCTIONS

Video analytics	Scene change detection, Face detection, Video tampering detection, Line crossing detection (human / vehicle classification), Region entrance / exit / intrusion detection (human / vehicle classification), Object abandoned / missing detection, Vehicles / people counting, Heat map
Privacy zones (n°)	4
Back light compensation (BLC)	BLC, HLC
Digital effects	Corridor mode (90° / 180° / 270° rotation), Defog, Mirror (Horizontal, Vertical, 180° rotation), ROI zones, Lens distortion correction
Wide Dinamic Range (WDR)	WDR (120dB)
Enhanced DNR control	3D-DNR
White balance control	Automatic, Indoor, Manual, Outdoor
Display brightness control	Yes
Image flip	Yes
Automatic gain control (AGC)	Yes
Camera titling	Yes

HARDWARE SPECIFICATIONS

IR LED lighting distance	3 led arrays / 30m (Smart IR)
Vandal Resistant rating (IK code)	IK10
IP protection rating	IP67
Audio Inputs/Outputs	1 (RCA) + 1 (microphone) / - (G.711u / G.711a)
LAN output type	Ethernet 10/100 Mbit/s (RJ45)
Support SD card (card not included)	Micro-SD (256GB max)

GENERAL DATA

Supply voltage	12VDC
Max absorption (W)	6.5
PoE power supply	Standard IEEE 802.3af
Type of power supply	PoE, External power supply



IPTCAMA04FB

IP TURRET CAMERA 4MP 2.8MM

GENERAL DATA

Diameter (mm)	108
Height (mm)	96
Product weight (g)	460
Type of finishing materials	Die-cast aluminum
Housing type	Turret
Product color	White
Operating temperature (°C)	-30 ÷ 60
Operating humidity (RH max) (%)	25 ÷ 95

**IPTCAMA04FB****IP TURRET CAMERA 4MP 2.8MM****ACCESSORIES****WMA-01A ADVANCE NEXT WALL-MOUNT BACKPLATE**

Wall-mounting support for Next and Advance cameras. For compatibility with models, please refer to the diagram in the downloads section.

**WMA-KTBBA ADVANCE NEXT WALL BACKPLATE**

Wall-mounting bracket for Next and Advance cameras. For model compatibility please refer to the diagram in the download section.

**CMA-KTBBA ADVANCE NEXT CEILING BACKPLATE**

Ceiling-mounting accessory for Next and Advance cameras. For model compatibility please refer to the diagram in the download section.

**JBA-TBBA ADVANCE NEXT CONNECTION BOX IP66**

Junction box for securing Next and Advance cameras. For model compatibility please refer to the diagram in the download section.

**PMA-A ADVANCE ADVANCE NEXT BEUGEL OP PAAL POLE-MOUNTING BACKPLATE**

Pole-mounting accessory for Next and Advance cameras. For model compatibility please refer to the diagram in the download section. Pole diameter from 80 to 140 mm

**AMA-A ADVANCE NEXT CORNER BACKPLATE**

Corner-mounting accessory for Next and Advance cameras. For model compatibility please refer to the diagram in the download section.