



**IPTCAMN08FA**

## **IP TURRET CAMERA 8MP, 2.8MM, AI**



### **NEXT SERIE**

Next series IP turret camera, 2.8 mm fixed lens, resolution 8MP@20 fps, IR LEDs with range of 30 metres (Smart IR), ONVIF compatible. Video analysis functions: Line crossing detection, Intrusion into an area detection. WDR 120Db, video compression H.265+ / H.265 / H.264+ / H.264 / MJPEG, SD slot (max. 256GB). Audio: 1 in, built-in microphone. IP67 waterproof die-cast aluminium enclosure, power supply 12 VDC / PoE IEEE802.3af. Compatible with browsers: IE/Google Chrome/Edge/Firefox/Safari. Compatible accessories: JBA-TBBA, CMA-KTBBA, WMA-KTBBA, PMA-A, AMA-A, WMA-01A.

### **AWARDS**





**IPTCAMN08FA**

**IP TURRET CAMERA 8MP, 2.8MM, AI**

**MAIN FEATURES**

Camera sensor	1/2.8" CMOS Ultra Starlight
Lens optical dimensions (mm)	2.8
Effective pixels (H x V - pixels)	3840x2160
Horizontal FoV (°)	100.4
Vertical FoV (°)	53
Diagonal FoV (°)	120
Electronic shutter (s)	1÷1/100000
Sensitivity	0.03 (colour), 0.001 (B/W), 0 (B/W, led IR ON)
Video trasmission	Triple streaming
Management software	Comelit CCTV Manager
Video resolution	4K (8MP)

**SOFTWARE/FIRMWARE SPECIFICATIONS**

Video compression	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Frame rate	20fps
Protocols supported	DHCP, FTP, HTTP, HTTPS, IPv4, IPv6, PPPoE, QoS, RTSP, UDP, ONVIF, RTMP
Updating firmware using network	Yes
Users connected at the same time	10 (live)
Remote viewer from browser	Edge, Firefox, Chrome, Safari
Remote control by mobile	APP Comelit CCTV

**FUNCTIONS**

Main functions	3D-DNR, BLC, Defog, HLC
Motion detection	396
Video analytics	Line crossing, enter area, Scene change detection, Video tampering detection, Blurred image detection
Privacy zones (n°)	4
Back light compensation (BLC)	BLC
Wide Dinamic Range (WDR)	WDR (120dB)



**IPTCAMN08FA**

**IP TURRET CAMERA 8MP, 2.8MM, AI**

**FUNCTIONS**

Enhanced DNR control	3D-DNR
White balance control	Automatic, Indoor, Manual, Outdoor
Exposure control	Auto
Display brightness control	Yes
Camera titling	Yes

**HARDWARE SPECIFICATIONS**

IR LED lighting distance	30m
Vandal Resistant rating (IK code)	IK10
IP protection rating	IP67
Audio Inputs/Outputs	1 (RCA) + 1 (microphone) / - (G.711u / G.711a)
LAN output type	Ethernet 10/100 Mbit/s (RJ45)
Support SD card (card not included)	Micro-SD (256GB max)

**GENERAL DATA**

Supply voltage	12VDC
Max absorption (W)	7.5
PoE power supply	Yes
Diameter (mm)	108
Height (mm)	96
Product weight (g)	460
Type of finishing materials	Die-cast aluminum
Housing type	Turret
Product color	White
Operating temperature (°C)	-30 ÷ 60
Operating humidity (RH max) (%)	25 ÷ 95

**IPTCAMN08FA****IP TURRET CAMERA 8MP, 2.8MM, AI****ACCESSORIES****WMA-01A    ADVANCE NEXT WALL-MOUNT BACKPLATE**

Wall-mounting support for Next and Advance cameras. For compatibility with models, please refer to the diagram in the downloads section.

**WMA-KTBBA    ADVANCE NEXT WALL BACKPLATE**

Wall-mounting bracket for Next and Advance cameras. For model compatibility please refer to the diagram in the download section.

**CMA-KTBBA    ADVANCE NEXT CEILING BACKPLATE**

Ceiling-mounting accessory for Next and Advance cameras. For model compatibility please refer to the diagram in the download section.

**JBA-TBBA    ADVANCE NEXT CONNECTION BOX IP66**

Junction box for securing Next and Advance cameras. For model compatibility please refer to the diagram in the download section.

**PMA-A    ADVANCE ADVANCE NEXT BEUGEL OP PAAL POLE-MOUNTING BACKPLATE**

Pole-mounting accessory for Next and Advance cameras. For model compatibility please refer to the diagram in the download section. Pole diameter from 80 to 140 mm

**AMA-A    ADVANCE NEXT CORNER BACKPLATE**

Corner-mounting accessory for Next and Advance cameras. For model compatibility please refer to the diagram in the download section.