



NIPNVR004A08PASL

4CH POE NVR, ADVANCE SERIES, NDAA, NO HDD



ADVANCE
SERIE

Network video recorder (NVR) for 4 IP channels (4 PoE), NDAA compliant, max. resolution 8 MP, video compression H.265S/H.265+/H.265/H.264, dual streaming, bandwidth 80 Mbps. Supports all DVA video analysis functions for the connected cameras. Number plate database.

Compatible with browsers: IE/Google Chrome/Edge/Firefox/Safari. Remote control via Comelit CCTV APP and Comelit CCTV Manager software. 48 V power supply unit included. This NVR connects to Comelit servers protected by AWS services.

AWARDS





NIPNVR004A08PASL

4CH POE NVR, ADVANCE SERIES, NDAA, NO HDD

MAIN FEATURES

Video inputs	4 PoE (4K/6MP/5MP/4MP/3MP/1080P/1280×1024/960P/720P/960H/D1/CIF)
Main video output	HDMI1: 3840 × 2160@30fps / 1920 × 1080 / 1280 × 1024 / 1024 × 768, VGA1: 1920 × 1080 / 1280 × 1024 / 1024 × 768.
Audio Inputs/Outputs	1 / 1
Video compression	H.265S / H.265+ / H.265 / H.264
Decoding live	1 × 8MP@30fps / 6 × 1080P@30fps
Decoding playback	1 × 8MP@30fps / 6 × 1080P@30fps
Playback / recording frame rate	30fps@8MP
Additional Hard Disks (SATA)	1 (10TB max)

SOFTWARE/FIRMWARE SPECIFICATIONS

Recording methods	Automatic, manual, programmed, event
Maximum number of channels being played simultaneously	1@4K, 6@Full HD
Audio compression	G711A/U
Protocols supported	DDNS, DHCP, HTTP, HTTPS, IPv4, IPv6, NTP, PPPoE, RTCP, RTP, RTSP, SMTP, TCP/IP, UDP, UPnP, IGMP, P2P, DNS, SNMP, IEEE 802.1x, ONVIF (Profile-S), ONVIF (Profile-G), ONVIF (Profile-T)
IP assignment	DHCP, manual
Max bandwidth (Mbps)	80
Remote control via browser	Edge, Firefox, Chrome, Safari
Remote control by software	Comelit CCTV Manager
Remote control by mobile	APP Comelit CCTV
Users connected at the same time	64
Main functions	Video analysis (only with dedicated cameras), Car park management function, Alarm system function, Two way audio
Car plate database [max. number of registrable plates]	1000



NIPNVR004A08PASL

4CH POE NVR, ADVANCE SERIES, NDAA, NO HDD

FUNCTIONS

Motion detection	Yes
System log	Yes

HARDWARE SPECIFICATIONS

Type of connections/ports	1 x Ethernet 10/100/1000 Mbit/s, 2xUSB 2.0, 4 x Ethernet PoE 10/100 Mbit/s
Fanless	Yes

GENERAL DATA

Machine absorption (no HDD) (W)	10
Maximum absorption per POE port (W)	30
POE total power (W)	48
Maximum distance in long range mode (CAT5e/CAT6) (m)	150
Power supply voltage (VDC)	48
Height (mm)	45
Width (mm)	300
Depth (mm)	249
Product weight (g)	2200
Type of finishing materials	Metallic
Product color	Black
Operating temperature (°C)	-10 ÷ 50
Operating humidity (RH max) (%)	25 ÷ 90
Supplied accessories	Power supply, Mouse