



RF1MCW

WIRELESS 1 INPUT MAGNETIC CONTACT, WHITE



The wireless magnetic contact RF1MCW has an auxiliary wired input for the connection and transmission of an independent zone in the control panel. The magnetic contact has two reed switches to allow flexible positioning of the external magnet. Excellent radio range and long battery life guarantee consistent performance over time. Colour: white.

AWARDS





RF1MCW

WIRELESS 1 INPUT MAGNETIC CONTACT, WHITE

MAIN FEATURES

Type of sensor	Magnetic contact
Wireless technology	Bidirectional protocol
Modulation	GFSK
Radio frequency band (MHz)	868.05 ÷ 869.95
Events Reported	Alarm, tamper, supervision, low battery
Monitoring	Yes
Tamper protection	2 anti-tamper and anti-tear
Trademarks/Certifications	EMC immunity EN 50130-4
	2 (right / left)
	NO, NC, EOL, DEOL

FUNCTIONS

Battery level control	Yes
	Yes
	Yes

HARDWARE SPECIFICATIONS

Type of finish	ABS
Colour	White
Operating temperature (°C)	-10 ÷ 50
Height (mm)	92
Width (mm)	22
Depth (mm)	25
Surface-mounted	Yes
	11 x 50 x 8

ELECTRICAL SPECIFICATIONS

Maximum current absorption (mA)	26
(µA)	4
Battery	1x lithium 3V type CR123 (included)



RF1MCW

WIRELESS 1 INPUT MAGNETIC CONTACT, WHITE

ELECTRICAL SPECIFICATIONS

Type contact	Reed
(V)	2.6