



RFSIR702

RADIO EXTRNAL SIREN, SERIES 2



RFSIR702 is a wireless siren with battery included, featuring many additional functions: tones or flashing on activation and deactivation, deterrent function, adjustable alarm tone volume and duration. Every setting can be changed remotely, without having to open up the siren. Several jumpers are provided for the main settings, allowing customised installation without the use of software.

AWARDS





RFSIR702

RADIO EXTRNAL SIREN, SERIES 2

MAIN FEATURES

Wireless technology	Bidirectional protocol
Radio frequency band (MHz)	868.05 ÷ 869.95
Sound pressure	102db@1m
	Yes
Alarm tone frequency (Hz)	2700 ÷ 3300
Max alarm tone duration (minutes)	30
Monitoring	Yes
Tamper	Anti-tamper and anti-tear
Knock light	Led
Other LED warning	Arming / Disarming, deterrent function, service mode
Trademarks/Certifications	EMC immunity EN50130-4
	Yes
	Yes
	Yes

HARDWARE SPECIFICATIONS

IP protection rating	IP34
Type of finish	ABS
Colour	White
Vandal Resistant rating (IK code)	IK08
Height (mm)	308
Width (mm)	208
Depth (mm)	69
Weight without battery (g)	1200
Operating temperature (°C)	-25 ÷ 60

ELECTRICAL SPECIFICATIONS

Maximum current absorption (mA)	26
(µA)	4



RFSIR702

RADIO EXTRNAL SIREN, SERIES 2

ELECTRICAL SPECIFICATIONS

(V)	5.4
Number and type of the battery	4 x CR17450 (custom battery pack)