

**UT1010VCB****ULTRA AUDIO REMOTE CAMERA MODULE, BLACK, SB1**

Audio module with facility for connection of an analogue remote camera with PAL standard for Ultra entrance panel, colour black RAL9005, Simplebus 1 system. For use in systems with power supply unit art. 1595 and art. 4888C. Easy to install and configure, thanks to smart call button programming. Twilight sensor for automatic nameplate backlighting power-off during daytime hours. Omnidirectional digital microphone and dual loudspeaker for high-fidelity audio. Audio-visual indications for disabled individuals assistance request can be activated via programming. Facility for 2 call buttons. To be finished with a cap, single button or double button in professional-grade plastic given an anti-yellowing and anti-dulling treatment or in aluminium. Regulation and programming without removing the module. ULTRA, the new and most technologically advanced entrance panel offering maximum ease of installation. Available in flush-mounted (10 mm protrusion from the wall) or surface-mounted (just 35 mm protrusion from the wall) variants. Dimensions (L x H x D): 100 x 90 x 35 mm.

AWARDS



UT1010VCB

ULTRA AUDIO REMOTE CAMERA MODULE, BLACK, SB1

GENERAL DATA

Type	Modular
Height (mm)	90
Width (mm)	100
Depth (mm)	35
Product weight (g)	275
Product color	Black RAL9005
Type of finishing materials	Polycarbonate, Aluminium alloy
Flush-mounted	Yes, with a dedicated accessory
Wall-mounted	Yes, with a dedicated accessory

COMPATIBLE SYSTEMS

Audio/video Simplebus 2 with power supply art. 4888C	Yes
--	-----

AUDIO FEATURES

Microphone	MEMS audio digital sensor, omnidirectional
Loudspeaker	28mm (Ø), 8 Ohm, 1W (2)

ELECTRICAL CHARACTERISTICS

Type of power supply	External power supply
Supply voltage	33VDC
Absorption in stand-by (W)	1.5
Maximum absorption (W)	4

HARDWARE FEATURES

Call type	Push-buttons
Type of buttons	Mechanical
Number of push-buttons (n°)	2
Backlight colour	White, Off
Clamps	L L V+ V- COM NC NO SE GND RTE TX- TX+ RX- RX+



UT1010VCB

ULTRA AUDIO REMOTE CAMERA MODULE, BLACK, SB1

HARDWARE FEATURES

Number of inputs (n°)	1
Number of outputs (n°)	2
Type of outputs	Relay (C-NO-NC, 4A@12÷24 VAC/VDC, 10A peak)
Communication ports	Micro-USB
Twilight sensor	Yes

SETTINGS

Loudspeaker volume	Yes
Microphone volume	Yes
Backlight brightness	Yes

PROGRAMMING MODE

Manual programming (via Dip Switch)	Yes
ViP Manager software	Yes

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection rating	IP65
Vandal Resistant rating (IK code)	IK08
Operating temperature (°C)	-25 ÷ 55
Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	IV
Certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

MAIN FUNCTIONS

Door opener	Yes
Number of auxiliary relays (n°)	1
Input for local door release button	Yes
Door open signaling input	Yes
Visual indications of system status	Yes



UT1010VCB

ULTRA AUDIO REMOTE CAMERA MODULE, BLACK, SB1

MAIN FUNCTIONS

Acoustic signals of system status	Yes
Speech synthesis of system status	Yes