



Product Code

F01491

## MEET 4 RELAY MODULE

Reference

EAN

1491

8424299014913

### Description.

#### Description

Meet panel 4 relay module, running under standard Modbus protocol, makes Meet monitors able to extend door release to 4 additional relays or doors. It works as a slave device connected to the RS-485 port of panel #1 of each block.

Extend relay unlock: Panel 4 Relay Module can increase control of up to 4 additional doors. The relay on the panel is still effective.

The additional relays can be activated from the monitor's user interface pressing the KEY icon. A list of available relays will be shown (if enabled) so the user can select which one activate.

In order to use this feature, the relays must be configured in both the panel and monitors.

For secure lock activation from indoor you must use ref. 1490: Meet External Doorlock Relay

#### Technical Details

##### Feeding:

- 7-26 Vdc (12Vdc recommended)
- Standby: 0.28W
- Maximum: 5.5W

##### Connections:

- RS-485 Modbus Bus

- Outputs of the 4 relays: COM/NO/NC

### Operational:

- Relay contacts: 220V/5A
- Status LEDs:
  - Power. On if powered.
  - RUN: Flashing after feeding.
  - LNK: Receiving a package at the last minute.
  - ACT: activity on the RS-485 bus.
- Relay activated: CH1-CH4

### Work environment:

- Temperature: -40 oC .. +55 oC
- Humidity: 10 – 95% (Non-condensed)
- IP: 51

### Dimensions:

- 115(W) x 90(H) x 40(D)mm
- Mounting on 35 mm DIN rail

### Details.

Product measurements (height x width x depth) mm	Weight (kg)	Packaging measurements (height x width x depth) cm	Video Door Entry system Technologie
115 X 90 X 40	0.21118	6,3x17,7x9,5	MEET

### Manuals

- 970086E Modulo 4 reles MEET ref 1491 V10\_21.pdf
- 970086I Modulo 4 reles MEET ref 1491 V10\_21.pdf

### Declaration of conformity

- DOCF01491EN.pdf

### Other images

