



Product Code
F01522

2/W VIDEO WAY 7" KIT

Reference	EAN
1522	8424299015224

Description.

Description

KIT

Includes:

- 1528 WAY 2/L plate with visor
- 1525 WAY Monitor 7" (x2)
- 1440 DIN8 26DC-2A Feeder

Extensions:

- HOUSING: up to 2 additional monitors (total 3) without the need for additional power.
- STREET PANEL: up to 1 additional street panel (total 2).

Additional cameras:

- An additional CCTV aerial analog camera can be installed on each street plate (up to 2 cameras in the same installation).

POWER SUPPLY. Ref. 1440

- Features: 100-240Vac, 0.6A (50-60Hz) / 26Vdc, 2A. DIN 8 rail mounting

PANEL. Ref 1528

- Surface mount. Rain visor included, required for mounting.

- Material finish: zamak and aluminum
- Connections (terminals S+, S-) for low-consumption 12 Vdc electric door opener. Maximum consumption of electric door opener: 250 mA in maintenance. Timer (1-8 s.).
- Potential-free relay for activation of 2nd door (garage): Configurable as Normally Open/Closed (COM, NO/NC). Timer (1-8 s.).
- Connection for hall exit button (PL, S+ terminals): Activates the electric door opener (S+, S-) while pressed.
- Card holder (with front extraction) and call button, both with LED backlighting. Backlight activation by light sensor.
- Speaker volume adjustment potentiometer.
- Connections (GND, CCTV) for additional analog CCTV camera.

MONITOR. Ref 1525

- Surface mount (wall connector included).
- 7” touch screen. Intuitive user interface supports swipe operations.
- LEDs: White: Monitor On; Purple: Do Not Disturb On; Green: Photos/Videos Pending to be Viewed
- Talk Mode: Hands-free
- Doorbell connections: GND, BELL terminals
- Date and time: Time: 24h format; Date: configurable format. Manually programmable from the monitor.
- Do not disturb mode: Immediate and/or timed activation/deactivation for a specific time slot during the day.
- Photo Capture: Automatic-Disableable (disabled by default) and manual. 100 photos without Micro SD card, 1,000 with Micro SD (not included in the kit). Photos on the monitor can be copied to the Micro SD card.
- Video capture: Automatic-Disableable (disabled by default) and manual. Only with 8-32 GB Micro SD card, not included in the kit. Up to 128 15 s videos.
- Delete photos and videos: One by one, select several, select all. When the storage limit is reached, the oldest ones are deleted. Option to format the Micro SD. Deletion after 30 days is activated by default.
- Call history (with date and time): Photos and videos are stored with date and time.
- Auto-on (street view from monitor): 2 license plates and 2 cameras. Selectable.
- Pedestrian door opening (electric door opener): Activates 12 Vdc output (S+, S- terminals on the board). Programmable opening time (1-8 s.)
- Garage door opening (electromagnetic door opener): Activates relay (COM, NO/NC terminals). Programmable opening time (1-8 s.)
- Image settings: Brightness, Contrast and Color.
- Call and conversation volume adjustment: 0-8 levels
- Internal intercom function in the home: Possibility of calling one or calling all. Maximum up to 3 monitors per home (1 Main and 2 Additional)
- Menu languages: 16
- Call melodies: 16. Selectable for: door panel call, door bell, intercom call.
- CCTV camera compatibility: One analog aerial camera per plate.
- Connections:

- Bus (B, B);
- Doorbell (GND, BELL);
- Micro SD card slot (8-32 GB);
- Impedance matching switch for the video signal (dipswitch 1 ON at the end of the line).
- Home address setting switch (dipswitch 2: OFF=Home 1; ON=Home 2)

Technical Details

PANEL. Ref 1528

Feeding

- Nominal: 24Vdc NON-POLARIZED (polarization is not taken into account during installation). It is powered directly from the Bus

Environmental

- Operating temperature: [-25ºC, +70ºC]
- Relative humidity (non-condensing): [5%, 95%]
- Waterproofing rating (IP): 44

Mechanics

- Dimensions (W x H x D): 94 x 164 x 21 (34 with visor) mm
- Impact resistance grade (IK): 07

Camera

- Angles: H=120º; V=90º
- Color night vision through white LEDs (6) with light sensor activation. As it has LEDs, no additional lighting is required.
- Camera resolution: 900 TVL

MONITOR. Ref 1525

Feeding

- Nominal: 24Vdc NON-POLARIZED (polarization is not taken into account during installation). It is powered directly from the Bus

Environmental

- Operating temperature: [-10ºC, +55ºC]
- Relative humidity (non-condensing): [5%, 95%]

- Waterproofing rating (IP): 30

Mechanics

- Dimensions (W x H x D): 222 x 154 x 11.5 mm

Touch screen

- Size: 7"
- Format: 16:9
- Resolution: 1024 x 600 pixels

Details.

Weight (kg)

2.466

Packaging measurements

(height x width x depth) cm

21x28,8x15

Video Door Entry system

Technologie

WAY

Manuals

- 970311 Guia rapida Kit Video Way 1L-2L V04_25.pdf

Declaration of conformity

- DOCF01522EN.pdf

Products included



F01440
P.S.U. DIN8 26VDC-2A



F01528
2/W COLOUR WAY VIDEO KIT PANEL



F01525
7" WAY KIT MONITOR

Training video

- https://www.youtube.com/playlist?list=PLf1YNFmssC3554qOXvGsVoRy3rwgEfja3