




Product Code

F01794

ELECTRIC STRIKE 540N-512 MAX

Reference

1794

EAN

8424299017945

Description.

Description

Operating type.

There are several types of door lock release mechanisms depending on the type of operation needed.

N-512 Inverted type 12Vdc (Inverted Operation and 12 Vdc activation)

The door release is automatically unlocked when the 12 Vdc pulse stops.

Reversible (Right DIN or Left DIN).

Lets you open the door from right and left.

Symmetrical.

Allows to change hands, maintaining the body symmetry.

DIN STANDARD

establishes the direction the door opens and designates the type of lock release installed.

Looking at the door from the side with the hinges visible:

- If the hinges are to the left of the observer, it is a left DIN lock release.
- If the hinges are on the observer's right, it is a right DIN.

Max Adjustable Latch:

The lock release includes an adjustable latch, allowing a perfect fit between latch and deadbolt in the lock, with a 4mm margin. It avoids door leaf pressure on the lock release latch bolt.

Technical Details

Consumption:

- N, At 12Vac: 560mA
- N-412 12Vdc: 260mA.
- N-424 24Vdc: 180mA.
- N-512 12Vdc: 200mA.
- N-524 12Vdc: 120mA.

Dimensions:

- 540 series, 67(V)mmx20.5(H)mmx28(P)mm

MAX Adjustable Latch: 3mm

Details.

Weight (kg)	Packaging measurements	Video Door Entry system
0.1685	(height x width x depth) cm	Technologie
	2,7x10,2x3,2	GENERICA