




Product Code

F01799

ELECTRIC STRIKE 540ND MAX

Reference

1799

EAN

8424299017990

Description.

Description

Operating type.

There are several types of door lock release mechanisms depending on the type of operation needed.

N type Normal 12 Vac. (Normal operation and 12 Vac activation).

The lock release is unblocked for the time that the 12 Vac voltage is applied.

Reversible (Right DIN or Left DIN).

Lets you open the door from right and left.

Symmetrical.

Allows to change hands, maintaining the body symmetry.

DIN STANDARD

establishes the direction the door opens and designates the type of lock release installed.

Looking at the door from the side with the hinges visible:

- If the hinges are to the left of the observer, it is a left DIN lock release.
- If the hinges are on the observer's right, it is a right DIN.

Max Adjustable Latch:

The lock release includes an adjustable latch, allowing a perfect fit between latch and deadbolt in the lock, with a 4mm margin. It avoids door leaf pressure on the lock release latch bolt.

D Unblocking

The door release includes a manual unblocking lever which inhibits its function, allowing free access.

Technical Details

Consumption:

- N, At 12Vac: 560mA
- N-412 12Vdc: 260mA.
- N-424 24Vdc: 180mA.
- N-512 12Vdc: 200mA.
- N-524 12Vdc: 120mA.

Dimensions:

- 540 series, 67(V)mmx20.5(H)mmx28(P)mm

MAX Adjustable Latch: 3mm

Details.

Weight (kg)

0.1665

Packaging measurements

(height x width x depth) cm

2,7x10,2x3,2

Video Door Entry system

Technologie

GENERICA