



Product Code

F02812

LOCK RELEASE 410AD-412-L22 MAX

Reference

2812

EAN

8424299028125

Description.

Description

Operating type.

There are several types of door lock release mechanisms depending on the type of operation needed.

A-412 type Automatic 12Vdc. (Automatic operation and 12 Vdc activation)

The lock release is triggered automatically when it receives a 12Vdc pulse. The lock release is blocked again once the voltage is cut off and the door opens and closes again mechanically. For proper installation, the automatic lock pin must be pressed in 3mm by the latch once the door is closed again.

Reversible (Right DIN or Left DIN).

Lets you open the door from right and left.

Symmetrical.

Allows to change hands, maintaining the body symmetry.

DIN STANDARD

establishes the direction the door opens and designates the type of lock release installed.

Looking at the door from the side with the hinges visible:

- If the hinges are to the left of the observer, it is a left DIN lock release.
- If the hinges are on the observer's right, it is a right DIN.

Serie 410

This door lock release is made up of an electric mechanism MOD.410 which dimensions are:

52,5(V)x16,4(H)mm. Recommended for replacement. The smallest door lock on the market (front width 16,5mm). Installed in smaller aluminium or PVC frames. Includes radial latch allowing the bolt to rotate on its axis without having to make a lateral cut in the door frame, which is not possible in traditional latch-bolt locks. The standard version offers MAX adjustable latch, allowing the adjustment between the latch and the bolt in the installation process.

Max Adjustable Latch:

The lock release includes an adjustable latch, allowing a perfect fit between latch and deadbolt in the lock, with a 4mm margin. It avoids door leaf pressure on the lock release latch bolt.

Flush mounted Door lock.

The electric lock release is a device installed in the door frame to control opening remotely using an electronic device. In an electric door entry system installation it is possible to activate the door lock of the building's entrance to allow the entry of the visit directly from the telephone or monitor just by pressing the doorlock key. The doorlock is made up of an electrical mechanism and a shield if it is flush mounted.

D Unblocking

The door release includes a manual unblocking lever which inhibits its function, allowing free access.

Type L22 flush shield.

For doors with deadbolt entry.

L22 type metallic trim fitted with an electrical mechanism to form a flush-fit lock release. Slightly narrower than standard width, recommended for smaller-sized aluminium and PVC frames.

Dimensions: 22(H)x250(V)mm.

Technical Details

Consumption:

- N, A 12Vac: 980mA
- N-412 12Vdc: 400mA.
- N-512 12Vdc: 200mA.

Details.

Weight (kg)

0.2255

Packaging measurements

(height x width x depth) cm

3,4x25x2,7

Video Door Entry system

Technologie

GENERICA