

Product Code

F02836

450N-M lock release

Reference	EAN
2836	8424299028361

Description.

Description

Operating type.

There are several types of door lock release mechanisms depending on the type of operation needed.

N type Normal 12 Vac. (Normal operation and 12 Vac activation).

The lock release is unblocked for the time that the 12 Vac voltage is applied.

Reversible (Right DIN or Left DIN).

Lets you open the door from right and left.

Symmetrical.

Allows to change hands, maintaining the body symmetry.

DIN STANDARD

establishes the direction the door opens and designates the type of lock release installed.

Looking at the door from the side with the hinges visible:

- If the hinges are to the left of the observer, it is a left DIN lock release.
- If the hinges are on the observer's right, it is a right DIN.

Serie 450

This door lock release is made up of a UNIVERSAL electric mechanisim model MOD.450, which dimensions are:
-75(V)mmx21(H)mm
Flush-mounted in wooden or metal frames. Its small size allows to change of hand without having to enlarge the space where the lock release is inserted.

Flush mounted Door lock.

The electric lock release is a device installed in the door frame to control opening remotely using an electronic device. In an electric door entry system installation it is possible to activate the door lock of the building's entrance to allow the entry of the visit directly from the telephone or monitor just by pressing the doorlock key. The doorlock it made up of an electrical mechanisim and a shield if it is flush mounted.

M type flush shield.

For doors with deadbolt entry.
M type metallic trim fitted with an electrical mechanism to form a flush-fit lock release.

Dimensions: 25(H)x250(V)mm.

Technical Details

Consumption:

- N,A 12Vac: 980mA
- N-412 12Vdc: 400mA.
- N-512 12Vdc: 200mA.

Details.

Product measurements (height x width x depth) mm	Weight (kg)	Packaging measurements (height x width x depth) cm	Video Door Entry system Technologie
75(V)mmx21(H)mmx28(P)mm	0.2785	3,4x25x2,7	GENERICA

Accessories



F02013
ADDITIONAL FUNCTIONS RELAY



F04802
P.S.U. DIN4 230VAC/12VAC-1A