

Product Code

F03450

DUOX PLUS iLOFT TELEPHONE



Reference

3450

EAN

8424299034508

Description.

Description

The iLOFT telephone is a compact, extra flat door phone that works in hands-free mode with the outdoor panel. Both the call and the talk volume are adjusted by means of a wheel control in a very intuitive way. Made of UV-resistant ABS plastic with an elegant matte finish for easy cleaning. Surface mounted. Push buttons: Button to activate/deactivate the communication with the outdoor panel. Door opener and call to the concierge (if available, press with the phone in standby). Additional functions button: Staircase light relay, second door or gate opening, panic call, etc.

System: DUOX PLUS (2-wire digital)

Technical Details

Note: from version V44.15 the phone is compatible with the CORA panel v01.03.003.

GENERAL CHARACTERISTICS

- Technology: DUOX PLUS (non-polarized 2 wire full digital system)
- Audio/Video system: Audio

- Set-up (Installation): Surface mounted
- Hands-free communication: Yes
- Press-to-talk communication configurable: Yes
- Color of the product: Matt white
- Number of pushbuttons: 3
- Kind of pushbuttons: Mechanical
- Number of leds for lighted indications: 3 (red, blue and green)

PROGRAMMING OF THE TERMINAL ADDRESS

- From the outdoor panel or guard unit: Yes
- From the outdoor panel throughout the apartment door bell: Yes

FEATURES

- Guard unit call: Yes (by means of the door release button when in standby)
- Auto-on: Yes (only with panel n° 0 of its own block)
- Additional function F1: Yes (Button F1 sends a negative and/or command)
- Apartment door bell differentiated from the outdoor panel: Yes
- Connection for additional devices (call extension, light/buzzer activator, etc.): Yes (ref. 2040, ref. 2438. Ref. 3467)
- Doormatic (automatic door release for offices, etc.): Yes (Green led indication)

ADJUSTMENTS

- Ring tones selection: Yes (5)
- Call volume control: Yes (by sliding wheel)
- Do-not-disturb mode: Yes (by sliding wheel) + red led indication
- Audio volume control: Yes (by sliding wheel)

TECHNICAL FEATURES

- Product dimensions (width x height x depth) mm 90 x 146,5 x 20
- Time to answer or open the door since the call is done: 30 s.
- Conversation time: 90 s.
- Conversation privacy: Yes
- Voltage: 18-24 Vdc
- Maximum consumption: 3.6 W
- Standby consumption: 0.4 W
- Working temperature (°C) [-5°C, +40°C]
- Humidity [0%, 90%]

- Product Weight (kg) 0,16
- Line adaptor included in the terminal Yes (A, C, default position OFF)
- Connections Bin, Bin, Bout, Bout, -, A+, F1, T

Details.

Weight (kg)

0.169447

Packaging measurements

(height x width x depth) cm

15x9,5x3,3

Video Door Entry system

Technologie

DUOX

Manuals

- 970113Ad_Man_Avanz_Telefono_iLOFT_DUOX_V07_21.pdf
- 970113Ed_Man_Avanz_Telefono_iLOFT_DUOX_V07_21.pdf
- 970113Fd_Man_Avanz_Telefono_iLOFT_DUOX_V07_21.pdf
- 970113Id_Man_Avanz_Telefono_iLOFT_DUOX_V07_21.pdf
- 970113Pd_Man_Avanz_Telefono_iLOFT_DUOX_V07_21.pdf
- 970114h_Telefono_iLOFT_Duox_Plus_V12_23.pdf
- 970146Fb Guia Usuario Telef iLOFT Duox Plus FRANCIA V04_20.pdf

Declaration of conformity

- DOCF03450EN.pdf

Accessories



F05636

iLOFT TEL. DESKTOP SUPPORT



F03388

UNIVERSAL FRAME



F03389

UNIVERSAL FRAME LARGE