



Product Code

F04825

POWER SUPP. UNIT+FILTER
DIN10 24VDC-2.5A

Reference

4825

EAN

8424299048253

Description.

Description

- Used to power the different equipment in a DUOX PLUS Fermax installation. Constructed in self-extinguishing V0 material.
- Includes a set of covers to protect the connection terminals.
- The POWER BUS terminals provide voltage and data. The PREV BUS terminals provides only data.
- It includes 2 leds: • ON • OVERLOAD: LED indicating maximum current limit exceeded. Reduce the load. LED ON + OVERLOAD blinking indicates short circuit.
- DIN-10 rail format for easy installation inside an electrical equipment box or can be screwed directly onto the wall.

Technical Details

- Dimensions DIN-10: 175x90x60 mm
- Input voltage: 110-240 Vac
- Input frequency: 50-60 Hz
- Output voltage: 24 Vdc $\pm 10\%$
- Output current: 2.5 A
- Efficiency at maximum load : 87% (for input 230V)
- Input protection: NTC fuse and 2. 5A
- Output protection: Overload of an electronic short circuit limitation
- Working temperature -5 ~ +45 °C
- Maximum humidity (without condensation) 95%

Details.

Product measurements (height x
width x depth) mm
90 x 175 x 60

Weight (kg)
0.5277

Packaging measurements
(height x width x depth) cm
6,5x18,1x9,6

Video Door Entry system
Technologie
DUOX

Manuals

- 970155 Fuente Alimentacion con Filtro 24Vdc Ref 4825
V06_24.pdf

Declaration of conformity

- DOCF04825EN.pdf