

GT-MKB-N

Video Guard Station

The GT-MKB-N video guard station is used to answer incoming calls, unlock the entrance, and trigger an optional output. It can also be used to call tenant stations, call entrance stations, and search for tenants via the directory. If concierge mode is engaged, calls can be screened for tenants.

There are two calling modes: standard calling via a tenant station and emergency calling via an urgent call switch. Standard calls emit a normal tone and display the name and number of the tenant. Emergency calls emit an urgent tone and display an alerting screen along with the name and number of the tenant. A standard call is reset by hanging up the handset. An emergency call must be reset at the tenant location.

The GT-MKB-N can be programmed three ways: manually, via a PC using the supplied USB cable, or via an Android™ device using NFC technology. A standard system supports two GT-MKB-Ns and an expanded system supports up to four.



- **3.5" screen**
- **Handset or hands-free communication**
- **Standard and internal emergency calls**
- **Communicates with entrance and tenant stations**
- **Calls to tenants can be screened with concierge mode**
- **Caller ID with call back**
- **Input for an optional JO-DV video door station**
- **Service button**
- **External signaling**
- **Program with PC or Android™ app**

Power Source 24V DC—use PS-2420UL

Communication Handset (full-duplex), hands-free (VOX), or push-to-talk (simplex)

Video Display 3.5" LCD screen

Mounting Surface mount to wall with 3-gang box or desk mount with included stand

Wire Type 2-cond., solid, non-shielded, PE insulation—use Aiphone #872002 for audio and #871802 for video and power

Weight ≈ 2.64 lbs (1.2 kg)

Dimensions 6 3/8" H 9 13/16" W 1 1/2" D