

**PAC 511 DCi** **Controllers**

The PAC 511 DCi is an intelligent IP access controller for securing and managing a single door. It can be deployed within a PAC access control system to support on-site access control, lift control and door functions either singularly or part of a larger PAC networked system. It relies on management software for many additional features but has in-built databases and processing ability to execute local access control and features associated with door management and lift control.

- Manages access through 1 door with a maximum of 2 readers (PAC or Wiegand) for full read-in and read-out capability
- Controls door lock via Fail Safe and Fail Secure modes
- Available in two variants:
  - DIN mount PAC 511 DCi for installation in optional PAC 4- or 6-way DIN cabinets
  - Boxed with pre-wired 3Amp PSU in a metal cabinet with lock and tamper switch for ease of install
- Up to 20,000 keyholder records in its onboard database
- Supports ongoing access control and lift control functions if communication to the management platform is lost
- One-Touch™ test mode
- Local anti-passback for accurate tracking of personnel



<b>Part Number(s)</b>	909032511 – 511 Controller - DCi, DIN mount	909030511 – 511 Controller - DCi, enclosure, 3.6A PSU <u>US markets</u> 909032511 – 511 Controller - DCi, enclosure, 3.6A PSU (USA)
<b>Number of Doors Supported</b>	One door with up to two access control devices as per the following options: <ul style="list-style-type: none"> <li>• An access control reader per door</li> <li>• An access control reader and Push To Exit (PTE) device per door</li> <li>• Two access control readers per door (read-in and read-out)</li> </ul>	
<b>Number of ID Devices Supported</b>	20,000	
<b>Supported ID Device Formats</b>	PAC (Cards and Tokens) Key PAC (Cards and Tokens) PAC Ops™ Lite (Cards and Tokens) PAC Ops™ (Cards and Tokens) Any card format supported by Wiegand	
<b>Event Storage</b>	20,000 events	

## PAC 511 DCi

## Controllers

<b>Configuration</b>	via PC with PAC Access Central or Easinet Residential software	
<b>Distance to Input Devices</b>	70m / 230ft (reader powered from controller) 500m / 1,640ft (locally powered reader)	
<b>Access Controller Input Devices</b>	PAC readers (LF, HF, MT, Architect and Biometric) & Wiegand readers PTE devices Door contacts Alarm inputs	
<b>Input Connection Features</b>	1 × tamper alarm input 1 × override input 1 × TCP/IP input (RJ-45) 1 × RS-485 input 1 × input per door channel	
<b>Output Connection Features</b>	1 × 5Amp ancillary relays, supporting programmable outputs. 3 x inputs for proactive monitoring: <ul style="list-style-type: none"> <li>• Tamper</li> <li>• Over-ride</li> <li>• Customer programmable input</li> </ul>	
<b>Recommended Cabling</b>	0.22mm 8-core alarm cable	
<b>System Power</b>	12–24 V DC	
<b>Power Input</b>	220-240V AC, 50Hz 110-120V AC, 60Hz (US)	
<b>Dimensions</b>	181 (w) × 65 (h) × 125 (d) mm 7.13 (w) × 2.56 (h) × 4.92 (d) in.	Boxed : 335 (w) × 335 (h) × 90 (d) mm Boxed: 13.19 (w) × 13.19 (h) × 3.54 (d) in.
<b>Weight</b>	909032511 — 0.61kg / 1.34lb	909030511 — 4.4kg / 9.7lb
<b>Operating Temperature</b>	0°C to +35°C / 32°F to 95°F	
<b>Operating Humidity</b>	10% to 85% Relative Humidity	
<b>Warranty</b>	5 years against electronic failure	
<b>Standards Compliance</b>	UKCA, CE, UL, FCC, IC, RoHS & WEEE compliant	