



RFBEAM10A

INFRARED RADIO MINI-BARRIER, HEIGHT 1M





RFBEAM10A

INFRARED RADIO MINI-BARRIER, HEIGHT 1M

MAIN FEATURES

Type	Pair of infrared RF barriers
Type of Detection	Infrared with synchronized pulse beams
Wireless technology	Bidirectional protocol
Radio frequency band (MHz)	868.05 ÷ 869.95
No. of IR rays	2Tx
Maximum outdoor distance (m)	5
Features IR beams	Pulsed, λ 950nm
Solar blinding protection	Up to 300,000lux
Synchronism	Optical TX / RX
Sensors logic	AND random
Barrier beams height control	Yes
Acoustic indicator TEST	Buzzer
Tamper protection	Si
Modulation	GFSK
Events Reported	Alarm, tamper, supervision, low battery
Monitoring	Yes

HARDWARE SPECIFICATIONS

Type of finish	Plastic
Operating temperature (°C)	-25 ÷ 65
Height (mm)	1220
Width (mm)	40
Depth (mm)	40
For outdoor use	Yes
Degree of protection	IP54

ELECTRICAL SPECIFICATIONS

Number and type of the battery	1 x 3,6V - 19Ah
--------------------------------	-----------------