

# Battery Backup

## Battery Backup - BBU 17-3A

Battery back up unit 3 amp (batteries not included)

## Battery Backup - BBU 17-5A

Battery back up unit 5 amp (batteries not included)

# Cables

Cables - CBL/12C0.5mm	6 pair cable - white, 0.5mm diameter CW 1308 - 100m
Cables - CBL/20C0.5mm	10 pair cable - white, 0.5mm diameter CW 1308 - 100m
Cables - CBL/2182Y	0.7mm twin cable for KV/2
Cables - CBL/2C 0.5mm2	2 core cable YY flexible grey 0.5mm2 CSA (100m) suitable for digital systems
Cables - CBL/8C 0.5mm2	8 core cable YY flexible grey 0.5mm2 CSA (100m) suitable for digital systems
Cables - CBL/8C0.5mm	4 pair cable - white, 0.5mm diameter CW 1308 - 100m
Cables - CBL/9502	2 twisted pair Belden style cable (100m)
Cables - CBL/9504	4 twisted pair Belden style cable (100m)
Cables - VCM/130 NPI	Composite cable 12-core plus 1 twisted pair, flame retardant - 150m
Cables - VCM/2D	Composite cable 2-core plus one twisted pair (100m) drum
Cables - VCM/40	Composite 3-core plus Coax, use between VT/1200 camera and VM/31 monitor -100m
Cables - VCM/4D	Composite cable 2-core plus three twisted pairs (100m) drum
Cables - VCM/60 NPI	Composite cable 5-core plus 1 twisted pair, flame retardant - 100m
Cables - VCM/60-11	Composite cable, as VCM/60, plus 11 cores @ 0.5sq mm - 100m
Cables - VCM/60-7	Composite cables, as VCM/60, plus 7 cores @ 0.5sq mm - 100m
Cables - VCM/130 CUT	As VCM/130 cut length to order - 1mt VCM/130 cable is sold in reels of 150 metres or shorter lengths cut to order (VCM/130 CUT). Should a different length be required (maximum length of 500 metres) this will be sold in a loose coil for lengths of 101 to 250 metres - this can be difficult to handle

Approximate weights without bobbins: 100 metres = 30 kg, 200 metres = 60/65 kg, 250 metres = 75 kg



## Cables (cont'd)

### Cables - VCM/130

Composite 12-core plus Coax, colour co-ordinated with terminals, use from PSU to entry panel - 150m

### Cables - VCM/60

Composite 5-core plus Coax, colour co-ordinated with terminals, use from PSU to monitor - 100m

### Cables - VCM/60 CUT

As VCM/60 cut length to order - 1m.

VCM/60 cable is sold in reels of 100 metres or shorter lengths cut to order (VCM/60 CUT). Should a longer length be required (maximum length of 500 metres) this will be sold in a loose coil for lengths of 101 to 250 metres - this can be difficult to handle.

Approximate weights without bobbins: 200 metres = 25 kg, 250 metres = 30 kg

## Keypads

### Keypads - INP/0243

Vandal resistant, storm coded access control unit, surface mounted



### Keypads - VRAC/F

Vandal resistant coded access control unit, flush mounted



### Keypads - VRAC/S

Vandal resistant coded access control unit, surface mounted



## Latch Releases

### Latch Releases - LR/1

Mortice latch release 8-12v AC - fail locked

### Latch Releases - LR/1B

As LR/1 in brass

### Latch Releases - LR/1R

Rim - fixing latch release 8-12v AC - fail locked

### Latch Releases - LR/1RB

As LR/1R in brass

### Latch Releases - LR/5

Mortice latch release 12V DC fail unlocked

### Latch Releases - LR/5R

Rim latch release 12V DC fail unlocked

## Lockable Enclosures

### Lockable Enclosure - ST3-315

IP65 lockable powder coated enclosure 300W x 300H x 150D (mm) comes with two keys

### Lockable Enclosure - ST4-515E

IP65 Lockable, powder coated, enclosure 400W x 500H x 150D (mm) comes with two keys

### Lockable Enclosure - ST5-520

IP65 Lockable, powder coated, enclosure 500W x 500H x 200D (mm) comes with two keys

### Lockable Enclosure - ST5-720

IP65 lockable powder coated enclosure 500W x 700H x 200D (mm) comes with two keys

## Magnets

### Magnets - EM/10000

Sliding door magnet 12v or 24v DC - holding force 650lbs/2.89kN (228L x 38W x 27D mm)

### Magnets - EM/10010

Single magnet 12v or 24v DC - holding force 1300lbs/5.79kN (268L x 75W x 40D mm)

### Magnets - EM/10060

Double magnet 12v or 24v DC - holding force 1300lbs/5.79kN (535L x 75W x 40D mm) 116.

### Magnets - EM/GATE-F

External magnet - monitored, 12V DC but with relay output to indicate door sealed. Holding force 1300lbs/5.79 KN (205L x 65W x 40Dmm)

## Miscellaneous

<b>AVT/300</b>	Remote camera interface	
<b>AZ/300</b>	Phonic group for vandal resistant entry panels only	
<b>BG/1</b>	Break glass button - resetable	
<b>DCR/100</b>	AC to DC rectifier, useful in installations where DC magnetic locks are used	
<b>DIC/100</b>	Interlock control unit, delays the opening of a second interlock door until the first door has closed	
<b>HIA/300</b>	Audio/video interface	
<b>ICP/LR</b>	Analogue entry panel encoder	
<b>KHPS</b>	Single button kit for Targha panels	
<b>KHPD</b>	Split button kit for Targha panels	
<b>KHSO</b>	Busy kit - takes up the space of one button	
<b>KHIN</b>	Information kit - takes up the space of two buttons	
<b>KHLV</b>	Accessory for green lighting of LED keys	
<b>RTE/2</b>	Green dome type exit switch - legend 'door release' - flush complete with back box. Stainless steel plate 85mm x 85mm N/O and N/C contacts	
<b>RTE/22</b>	Request to exit button (no back box) normally open contacts at 1 Amp/24 VDC - engraved 'Door Release'	
<b>RTE/2SURF</b>	Surface housing for RTE/2 40mm deep	
<b>Surface Housing for RTE/3</b>	Narrow style exit switch - legend 'door release' - flush complete with back box. Stainless steel plate 85mm x 40mm N/O and N/C contacts	
<b>SRT/101</b>	Special operation relay enabling timed or set-reset operation	
<b>TFL/101</b>	Timed flashing lamp - useful for the hard of hearing, can activate when a handset has been called	

## Miscellaneous (cont'd)

<b>TT/2</b>	Tradesman timer unit with LCD display - 7 day timer, 6 daily on/off times, many features
<b>VAL/90</b>	Video signal booster - for long runs up to 1,000m from monitor to entry panel. Sited close to monitor
<b>VRFS/DL</b>	Fireman's switch - vandal resistant, flush panel with drop key (140H x 140W x 65D mm)
<b>VRTB/F</b>	Vandal resistant tradesman's button - flush 140H x 140W x 60D mm



## Mounting & Embedding Boxes

<b>HBP/M</b>	Wall mounting box-inox
<b>HTS GR</b>	Chassis and embedding box, in grey
<b>HTS GH</b>	Chassis and embedding box, in light grey
<b>HTI</b>	Embedding box, in light grey
<b>HTT</b>	Embedding chassis, in light grey

## Posts

<b>Posts - HDP/DUAL</b>	Heavy duty, box section, dual height post, 1.2m/2m	
<b>Posts - HDP1200</b>	As HDP/DUAL but 1.2m high	
<b>Posts - HDP2000</b>	Heavy duty, box section, stainless steel post with adapter plate for entry panel 2m high (80x80mm)	
<b>Posts - TP1200</b>	Tubular, polished stainless steel post with adapter plate for entry panel 1.2m high 38mm diameter	