



DNR6352M

Ultra High Resolution True Day/Night Camera



DNR6352M

Key Features

- 1/3" Sony Super HAD CCD
- Ultra High Resolution, 600 TVL
- Digital Noise Reduction (DNR)
- Mechanical IR Cut Filter
- Maximum Sens-Up x512
- On Screen Display (OSD)
- Selectable Electronic Shutter Control
- Selectable White Balance
- Selectable Back Light Compensation
- Selectable Gain Control
- Privacy Masking
- Motion Detection
- Mirror Function



www.geniecctv.com sales@geniecctv.com T: +44 (0) 1707 330 541 F: +44 (0) 1707 330 543

Genie CCTV Ltd. CCTV House, City Park, Watchmead, Welwyn Garden City, Hertfordshire, AL7 1LT, United Kingdom



DATASHEET

www.geniecctv.com sales@geniecctv.com T: +44 (0) 1707 330 541 F: +44 (0) 1707 330 543

Genie CCTV Ltd. CCTV House, City Park, Watchmead, Welwyn Garden City, Hertfordshire, AL7 1LT, United Kingdom

Technical Specification

| · · | |
|--------------------------|--|
| Model Number | DNR6352M |
| Image Sensor | Sony 1/3" Super HAD High Sensitivity Colour CCD |
| Horizontal Resolution | 600 TVL (Colour), 700 TVL (B&W) |
| Sensitivity (F1.2) | 0.15Lux 40 IRE (Colour) 0.01Lux 40 IRE (B&W) |
| Scanning System | 2:1 Interlace |
| Effective Pixels (H x V) | 752 (H) x 582 (V) |
| Video Format | PAL |
| Synchronisation | INT / LL |
| Frequency | Horizontal : 15.625 KHz, Vertical : 50.00 Hz |
| Shutter Speed | 1/60,1/50 ~ 1/120,000 Sec |
| IR Cut Filter | YES |
| Gain Control | LOW / HIGH / OFF |
| Back Light Compensation | ON/OFF |
| Blemish Compensation | 256 Point (Even 128 Point, Odd 128 Point) |
| White Balance | ATW / AWC / MANUAL (1700°K ~11,000°K) / INDOOR / OUTDOOR |
| S/N Ratio | 52dB (AGC Off, Weight ON) |
| Sens-Up | AUTO / OFF (Selectable x2 ~ x512) |
| OSD | YES |
| Motion Detection | ON / OFF (8 Zone, ALARM Output) |
| DNR | ON / OFF (1~32 Level) |
| Mirror / Flip | Built-In |
| Privacy Function | ON / OFF (12 Zones) |
| Day / Night | COLOUR / B&W / EXTERN / AUTO |
| Sharpness | ON/OFF (Level Adjustable) |
| Iris Control | DC / Video |
| Lens Mount | CS Mount (Easy Focus type) (C Mount is Mountable by using Adaptor) |
| Power Consumption | MAX. 4.5W |
| Power Supply | AC230V |
| Operating Conditions | Temperature : -10°C to + 50°C, Humidity : 30% to 80% RH |
| Storage Conditions | Temperature : -20°C to + 60°C, Humidity : 20% to 90% RH |
| Dimensions (L x W x H) | 109.9 x 64 x 65.4 mm |
| Weight | Approx. 280g |

Features and specifications are subject to change for further improvement without any notice

Accessories

- CWB-130 Adjustable Bracket for Box Camera, M6 Screw Fixing, Ivory
- CWB-130S Adjustable Bracket for Box Camera, M6 Screw Fixing, Silver
- BR-01S Fully Cable Managed Box Camera Bracket, M6 Screw Fixing, Silver
- BR02W Cable Managed Metal Wall Mount Camera Bracket, White
- FILTERKIT4 Filter Set Up Kit
 - * Please see the Lens Section for Suitable Lenses