

ELECTRIC STRIKE 300Aa



Reference: 01709

Reversible (Right DIN or Left DIN).

Allows to open the door from right and left.

Non-symmetrical.

Allows to change hands while taking into account that the body does not keep symmetry with the...

DESCRIPTION

Reversible (Right DIN or Left DIN).

Allows to open the door from right and left.

Non-symmetrical.

Allows to change hands while taking into account that the body does not keep symmetry with the change from RIGHT DIN to LEFT DIN.

DIN STANDARD

establishes the direction the door opens and designates the type of lock release installed.

Looking at the door from the side with the hinges visible:

- If the hinges are to the left of the observer, it is a left DIN lock release.

-If the hinges are on the observer's right, it is a right DIN.

Operating type.

There are several types of door lock release mechanisms depending on the type of operation needed.

Type Aa Automatic Invisible 12Vac. (Invisible Automatic Operation and 12 Vac activation).

The lock release is unblocked automatically when it receives a 12Vac voltage pulse. The lock release is blocked again once the voltage is cut off and the door opens and closes again mechanically. It is designated invisible because it does not have the normal automatic lock pin.

TECHNICAL SPECIFICATIONS

Consumption:

N, A 12Vac: 980mA

N-412 12Vdc: 200mA.

N-512 12Vdc: 150mA.

N-424 24Vdc: 120mA.

Weight: 0,2180 kg

Size of product when packed: 3,4x16,3x2,7 cm

EAN 13: 8424299017099

