

ELECTRIC STRIKE 450ND-412



Reference: 01702

Reversible (Right DIN or Left DIN).

Lets you open the door from right and left.

Symmetrical.

Allows to change hands, maintaining the body

symmetry.

DESCRIPTION

Reversible (Right DIN or Left DIN).

Lets you open the door from right and left.

Symmetrical.

Allows to change hands, maintaining the body symmetry.

DIN STANDARD

establishes the direction the door opens and designates the type of lock release installed.

Looking at the door from the side with the hinges visible:

- If the hinges are to the left of the observer, it is a left DIN lock release.
- -If the hinges are on the observer's right, it is a right DIN.

Operating type.

There are several types of door lock release mechanisms depending on the type of operation needed.

N-412 Normal type 12Vdc (Normal operation and 12 Vdc activation).

The lock release is unblocked for the time that the 12 Vdc voltage is applied.

D Unblocking

The door release includes a manual unblocking lever which inhibits its function, allowing free access.

TECHNICAL SPECIFICATIONS

Consumption:

N, A 12Vac: 980mA N-412 12Vdc: 400mA. N-512 12Vdc: 200mA.

Weight: 0,1850 kg

Size of product when packed: 2,7x10,2x3,2 cm

EAN 13: 8424299017020