



Ref.02447 CITYMAX ADS BASIC MONITOR

■ DESCRIPTION

Video door entry B/W monitor. Flat screen 4".

Installed in homes, lets you communicate with the outside panel, open the door and see the visitor on the built-in screen .

Extra flat format monitors, manufactured in high impact ABS plastic with a mirror polish type finish for easy cleaning.

VDS system:

Simplified installation audio and video door entry system that does not use house call wires. The call is made by transmission of a digital call code generated by the VDS amplifier.

- In new works, installation can be carried out with the following type of wiring: UTP CAT5 / 5 wire / 3 wire + Coaxial (video).

Lets you manage up to 199 homes, 2 entrance accesses and a central guard unit.

Maximum distance from first access to last home: 200 m.

- In replacement works, the change from analogue entry to video entry system can be done taking advantage of the existing wiring.

The system capacity and distance will depend on the installation wiring.

VDS amplifier comes with voice synthesizer as standard issue.

When the door release is activated a message is heard: "Door open, please close after entering".

The home terminals require simple programming done from the outdoor panel. By means of this programming a call code is assigned to each terminal (telephone or monitor).

Communication is private.

Wiring. Audio: 3-wire bus. Video: UTP CAT5 / 5 wire / 3 wire + Coaxial (video).

Maximum distance from first access to last home: 200 m.

■ TECHNICAL SPECIFICATIONS

Flat screen 4".

Resolution: 480 (H) x 250 (V) lines.

Dimensions: 195x211x60 mm (height-width-depth):

Power supply: 18 Vdc

Door release and guard unit call button.

Auto-on button for main camera activation.

Auto-on button for 2nd access camera activation.

Button available for additional function: stairlight activation, garage door, etc. ...

Brightness and contrast control.

On/off control

Door bell: for direct house call button connection to monitor/telephone.

Two selectable call tones.

Private communication. Conversation secrecy.

Consumption:

- in standby: 15 mA

- active: 350 mA

Size of product when packed: 22,2x28,5x10,2

Weight: 1,400 kg

EAN 13: 8424299024479