



Ref.02451 VDS BASIC CITYMAX TELEPHONE

■ DESCRIPTION

Audio terminal. Installed in homes, enables communication with outdoor panel and door opening.

Fermax extra-flat format phones are manufactured in high impact ABS plastic with a mirror polish type finish for easy cleaning.

The industrial design applied and the top quality components give shape to a robust and reliable telephone that will equally please both professional and user.

Easy to fit wall mounted installation.

Models available with 1, 3 or 6 pushbuttons.

VDS system:

Simplified installation audio and video door entry system that does not use house call wires. The call is made by transmission of a digital call code generated by the VDS amplifier.

- In new works, installation can be carried out with the following type of wiring: UTP CAT5 / 5 wire / 3 wire + Coaxial (video).

Lets you manage up to 199 homes, 2 entrance accesses and a central guard unit.

Maximum distance from first access to last home: 200 m.

- In replacement works, the change from analogue entry to video entry system can be done taking advantage of the existing wiring.

The system capacity and distance will depend on the installation wiring.

VDS amplifier comes with voice synthesizer as standard issue.

When the door release is activated a message is heard: "Door open, please close after entering".

The home terminals require simple programming done from the outdoor panel. By means of this programming a call code is assigned to each terminal (telephone or monitor).

Communication is private.

Wiring. Audio: 3-wire bus. Video: UTP CAT5 / 5 wire / 3 wire + Coaxial (video).

Maximum distance from first access to last home: 200 m.

■ TECHNICAL SPECIFICATIONS

Screw-on surface assembly.

Power supply: 18 Vdc

Door release and guard unit call button.

Door bell: for direct house call button connection to monitor/telephone.

Two selectable call tones.

Private communication. Conversation secrecy.

Consumption:

- in standby: 5 mA.

- in call 220 mA

- active: 15 mA

Size of product when packed: 5x26x8

Weight: ,3018344 kg

EAN 13: 8424299024516