



## Ref.02452 VDS EXTRA CITYMAX TELEPHONE

---

### ■ DESCRIPTION

Audio terminal. Installed in homes, enables communication with outdoor panel and door opening.

Extra flat format monitors, manufactured in high impact ABS plastic with a mirror polish type finish for easy cleaning.

VDS system:

Simplified installation audio and video door entry system that does not use house call wires. The call is made by transmission of a digital call code generated by the VDS amplifier.

- In new works, installation can be carried out with the following type of wiring: UTP CAT5 / 5 wire / 3 wire + Coaxial (video).

Lets you manage up to 199 homes, 2 entrance accesses and a central guard unit.

Maximum distance from first access to last home: 200 m.

- In replacement works, the change from analogue entry to video entry system can be done taking advantage of the existing wiring.

The system capacity and distance will depend on the installation wiring.

VDS amplifier comes with voice synthesizer as standard issue.

When the door release is activated a message is heard: "Door open, please close after entering".

The home terminals require simple programming done from the outdoor panel. By means of this programming a call code is assigned to each terminal (telephone or monitor).

Communication is private.

Wiring. Audio: 3-wire bus. Video: UTP CAT5 / 5 wire / 3 wire + Coaxial (video).

Maximum distance from first access to last home: 200 m.

### ■ TECHNICAL SPECIFICATIONS

Dimensions: 195x211x60 mm (height-width-depth):

Power supply: 18 Vdc

Door release and guard unit call button.

Door bell: for direct house call button connection to monitor/telephone.

Two selectable call tones.

Complet Model - 2 additional pushbuttons without functions assigned.

Also available in the following variants (add the following variant number to the reference and increase price):

- VARIANT 1: Panic Button + (price increase).
- VARIANT 2: Volume Control with LED + (price increase).

Private communication. Conversation secrecy.

Consumption:

- in standby: 5 mA.
- in call 220 mA
- active: 15 mA

Size of product when packed: 5x26x8

Weight: ,3493344 kg

EAN 13: 8424299024523