

TECHNICAL DATA SHEET

KB-545 I/JS

3 Axis Controller



Front View



Overhead View

KEY FEATURES

- Controls A Wide Range Of Cameras, PTZ Domes and DVRs
- Controls Genie PTZs and GDVR series DVRs
- Multi Protocols (Baud Rate Selectable)
- RS485 Communication
- Variable Manual Control Speed
- Programmable User Preferences (Preset, Tour, Pattern, etc.)
- Easy Upload Programmed Data via Serial Communication
- USB Port (USB Cable Included)
- User Password Support
- Graphical Display
- Worldwide Switch Mode PSU Adaptor Included

ORDERING INFORMATION

KB545 I/JS 3 Axis Controller, Black



Rear View

TECHNICAL SPECIFICATION

Model Number	KB-545 I/JS
Keyboard Communication	Interface: RS-485 (Tx 3 Port, TRx 1 Port), Pan / Tilt Operating Distance 1029m
Connector Type Data	Terminal Block (8p)
Protocols	Protocols: Pelco D, Pelco P (Baud Rate Selectable)
Controller	Joystick Type, 3-Axis, Variable Speed with Zoom
LCD Display	16 x 2 Graphic Display
Input Voltage	DC 12V Or 9V Battery
Operating Conditions	Temperature: 0°C ~ 45°C, Humidity: 10% ~ 70%
Power Consumption	140mA max
Dimensions (W x H x D)	280 x 92 x 174 mm
Weight	700g

Features and specifications are subject to change for further improvement without any notice