

Door Entry Keypad Range



Access Keypad

Technical specifications

KP1000

- Keypad only

- Internal/External use only if fitted with RGL Rain Shield.
- 12vDC.
- Selectable backlit feature.
- Lock and Aux outputs.
- 500 unique users.
- PCB formal coated.
- Security screw.

KPX1000

- Built in prox reader.
- Uses EM cards or fobs
- Keypad or prox.
- 2 Open door modes

KPX2000

- Built in prox reader.
- Input for separate Wiegand reader.
- Uses EM cards or fobs
- Keypad or prox.

KP-FOB-BE	Proximity Fob - Blue
KP-FOB-GY	Proximity Fob - Grey
KP-CARD	Proximity Card - Standard

KPX2000	120x76x25 (mm)	Keypad with Prox & Reader Option	558g (Boxed) / 418g (Unboxed)
KPX1000	120x76x25 (mm)	Keypad with Prox	558g (Boxed) / 418g (Unboxed)
KP1000	120x76x25 (mm)	Keypad only	526g (Boxed) / 418g (Unboxed)

Other items in the RGL range.



Access Control

FEATURES

- Stylish design.
- Audio key operation.
- Door bell facility.
- Single or dual modes using Aux output.
- Individually programmable outputs
- Adjustable output timers on both Lock and Aux
- Zinc alloy electroplated casing.
- Surface mounted.

